

INDUSTRIAL COMPONENT DATA

**+IZMX-M40-48DC-1 184257 Y7-184257 EATON ELECTRIC
Motor operator 48 VDC. Can only be sold assembled.**

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-M40-48DC-1



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-M40-48DC-1
Catalog number	Y7-184257
Category	Motor operator for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-B4443AC136
Generated	2026-08-03

Product Overview

Motor operator 48 VDC. Can only be sold assembled.

+IZMX-M40-48DC-1

Motor operator 48 VDC

Accessories, Motor operator, The motor automatically arms the spring-operated stored energy mechanism for remote or local actuation and is therefore always ready for switching., Maximum operating frequency Actuations/minute 3, Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage U_s 48 V DC V, Operating range x US 0,85 - 1,1 Factor, max. Betriebsstrom I_n 3 A, max. Anlaufstrom (35ms) I_n 13.5 A, max. Leistung AC/DC 175 VA/W, max. Anlaufleistung (35ms) AC/DC 3 VA/W, For use with IZMX40..., INX40...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

Additional Product Information

Motor operator 48 VDCAccessories, Motor operator, The motor automatically arms the spring-operated stored energy mechanism for remote or local actuation and is therefore always ready for switching., Maximum operating frequency Actuations/minute 3, Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage U_s 48 V DC V, Operating range x US 0,85 - 1,1 Factor, max. Betriebsstrom I_n 3 A, max. Anlaufstrom (35ms) I_n 13.5 A, max. Leistung AC/DC 175 VA/W, max. Anlaufleistung (35ms) AC/DC 3 VA/W, For use with IZMX40..., INX40...

General specificationsProduct nameEaton Moeller series IZMX/INX motor operatorPart

no.+IZMX-M40-48DC-1EAN4015081796946Product Length/Depth200 millimetreProduct height100 millimetreProduct width150 millimetreProduct weight1.25 kilogramCompliancesRoHS conformProduct TradenameIZMX/INXProduct

TypeAccessoriesProduct Sub TypeMotor operatorDelivery programTypeAccessorySpecial featuresSignalling switch for
"Spring-operated stored energy mechanism tensioned" message is included as standard.

Switching frequency = 60/h

The motor automatically arms the spring-operated stored energy mechanism for remote or local actuation and is therefore always ready for switching.Used withIZMX40...

INX40...Technical Data - ElectricalVoltage typeDCControl voltage operating range0.85 - 1.1 x Us

48 V DCRated control supply voltage (Us) at AC, 50 Hz - min0 VRated control supply voltage (Us) at AC, 50 Hz - max0
VRated control supply voltage (Us) at AC, 60 Hz - min0 VRat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-M40-48DC-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.