

INDUSTRIAL COMPONENT DATA

IZMX-RP16A-200 124027 0004357380 EATON ELECTRIC

Rating plug, 200A, IZMX16, lu to 800A

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX-RP16A-200



Manufacturer	EATON - MOELLER
MPN / Reference	IZMX-RP16A-200
Catalog number	0004357380
Category	Current transformer
Minimum order	1 Pcs
Document ID	EO-DF060B144A
Generated	2026-08-06

Product Overview

Rating plug, 200A, IZMX16, lu to 800A

Rate current module for adapting to changes in the basic conditions for an application. The rate current module's nominal value must be less than or equal to the basic device's rated current. The rate current module can be replaced on site without replacing the transformer. Rate current module 200 A, 250 A and 300 A can be combined with P-trip units. The rate current module's nominal value must be less than or equal to the basic device's rated current. The rate current module can be replaced on site without replacing the transformer. Rate current module 200 A, 250 A and 300 A can be combined with P-trip units.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

Additional Product Information

EL-Nummer (Norway)0004357380Rating plug, 200A, IZMX16, lu to 800ARate current module for adapting to changes in the basic conditions for an application. The rate current module's nominal value must be less than or equal to the basic device's rated current. The rate current module can be replaced on site without replacing the transformer. Rate current module 200 A, 250 A and 300 A can be combined with P-trip units. The rate current module's nominal value must be less than or equal to the basic device's rated current. The rate current module can be replaced on site without replacing the transformer. Rate current module 200 A, 250 A and 300 A can be combined with P-trip units.Delivery program Product rangeAccessoriesAccessoriesOptions / accessories trip blocksAccessoriesRating Plug (rate current module)The rated current can be reduced by changing the rating plug, for example, in order to adapt to changed conditions in the application.

The rating plug's nominal value must be less than or equal to the basic device's rated current.

The rating plug can be replaced on site without replacing the transformer.

200 A, 250 A and 300 A rating plugs cannot be combined with P-trip units. Rated current [In] 200 A Suitable for circuit-breaker
lu=lu? 800 A For use with IZMX16 Design verification as per IEC/EN 61439

Operating ambient temperature min. -25 °C Operating ambient temperature max. +70 °C Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Current transformer (EC002048) Electr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX-RP16A-200 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.