


INDUSTRIAL COMPONENT DATA

IZMX-RP16B-400 124034 EATON ELECTRIC Rating plug, 400A, IZMX16, lu 1000A-1250A

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX-RP16B-400



Manufacturer	EATON - MOELLER
MPN / Reference	IZMX-RP16B-400
Catalog number	124034
Category	Current transformer
Minimum order	1 Pcs
Document ID	EO-9A3158F1CD
Generated	2026-08-04

Product Overview

Rating plug, 400A, IZMX16, lu 1000A-1250A

Rate current module for adapting to changes in the basic conditions for an application. The rate current module's nominal value must be less than or equal to the basic device's rated current. The rate current module can be replaced on site without replacing the transformer. Rate current module 200 A, 250 A and 300 A can be combined with P-trip units.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

Additional Product Information

Fuse-link, LV, 630 A, AC 400 V, NH3, gFF, IEC, dual indicator, insulated gripping lugs Fuse, fuse-link, low voltage, 630 A, AC 400 V, NH3, gFF, IEC, dual (combination) indicator system, square-body with knife blade contacts, insulated gripping lugs, IEC 60269-1. Breaking capacity 120 kA [Delivery program

Product range Fuse Field of application low voltage Rated current [I] 630 A Rated voltage AC 400 V Construction size NH3 Utilization category gFF Status indicator dual indicator Description insulated gripping lugs Breaking Capacity 120 kA Standard/Approval IEC Shape square-body with knife blade contacts Standards/Regulations IEC 60269-1 Optional accessories fuse-holder SD3-D , Design verification as per IEC/EN 61439

Rated operational current for specified heat dissipation [In] 630 A Equipment heat dissipation, current-dependent [Pvid] 44 W , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015]) Construction size NH3 Rated current 630 A Rated voltage 400 V Voltage type AC Rated switching capacity

120 kA Utilization category Other Type of fuse status indicator Combination fuse status indicator Insulated metal gripping lugs (IMGL) Yes]

ETIM for 124034 Low-voltage industrial controls and switchgear (EC002048)

Feature Name

Feature Value

Model (EF000010)

Through-feed....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX-RP16B-400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.