


INDUSTRIAL COMPONENT DATA

+IZMX-RR230AD-40-1 184124 68D2806G52 EATON ELECTRIC Reset remote, 220-240VAC/DC. Can only be sold assembled.

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-RR230AD-40-1



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-RR230AD-40-1
Catalog number	68D2806G52
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-87E18FB28F
Generated	2026-08-05

Product Overview

Reset remote, 220-240VAC/DC. Can only be sold assembled.

+IZMX-RR230AD-40-1

Reset remote, 220-240VAC/DC

Accessories, Remote reset, The circuit-breaker is equipped with a mechanical trip indicator (red pin)., After the remote reset coil is electrically actuated, the reclosing lockout can be reset., Cannot be combined with remote reset., Rated control voltage Us 208 - 240 V AC 50/60 Hz, 208 - 250 V DC V, For use with IZMX40...W IZMX40...F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers IZM**

Additional Product Information

Reset remote, 220-240VAC/DCAccessories, Remote reset, The circuit-breaker is equipped with a mechanical trip indicator (red pin)., After the remote reset coil is electrically actuated, the reclosing lockout can be reset., Cannot be combined with remote reset., Rated control voltage Us 208 - 240 V AC 50/60 Hz, 208 - 250 V DC V, For use with IZMX40...W IZMX40...F

Delivery program

Product rangeAccessoriesAccessoriesTrip indication / Reset optionsAccessoriesRemote resetThe circuit-breaker is equipped with a mechanical trip indicator (red pin).

After the remote reset coil is electrically actuated, the reclosing lockout can be reset.

Cannot be combined with remote reset.Rated control voltage [Us]208 - 240 V AC 50/60 Hz

208 - 250 V DC VFor use withIZMX40...W

IZMX40...FDesign verification as per IEC/EN 61439

Operating ambient temperature min.-25 °C Operating ambient temperature max.+70 °C Technical data ETIM 7.0
Low-voltage industrial components (EG000017) / Shunt release (for power circuit breaker) (EC001023) Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Full load current trip ( [AKF016013]) Rated control supply voltage U_s at AC 50 Hz 208 - 240 V Rated control supply voltage U_s at AC 60 Hz 208 - 240 V Rated control supply voltage U_s at DC 220 - 250 V Voltage type for actuating AC/DC Initial value of the undelayed short-circuit release - setting range 0 A End value adjustment range undelayed short-circuit release...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-RR230AD-40-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.