


INDUSTRIAL COMPONENT DATA

**+IZMX-RR24DC-40-1 184122 68D2806G53 EATON ELECTRIC
184122 +IZMX-RR24DC-40-1. Can only be sold assembled.**

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-RR24DC-40-1



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-RR24DC-40-1
Catalog number	68D2806G53
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-91A00EA699
Generated	2026-08-02

Product Overview

184122 +IZMX-RR24DC-40-1. Can only be sold assembled.

+IZMX-RR24DC-40-1

Reset remote, 24VDC

Accessories, Remote reset, The circuit-breaker is equipped with a mechanical trip indicator (red pin)., After the remote reset coil is electrically actuated, the reclosing lockout can be reset., Cannot be combined with remote reset., Rated control voltage Us 24 V DC V, For use with IZMX40...W IZMX40...F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers IZM
--------------	--

Additional Product Information

Reset remote, 24VDCAccessories, Remote reset, The circuit-breaker is equipped with a mechanical trip indicator (red pin)., After the remote reset coil is electrically actuated, the reclosing lockout can be reset., Cannot be combined with remote reset., Rated control voltage Us 24 V DC V, For use with IZMX40...W IZMX40...FDelivery program
Product rangeAccessoriesAccessoriesTrip indication / Reset optionsAccessoriesRemote resetThe circuit-breaker is equipped with a mechanical trip indicator (red pin).

After the remote reset coil is electrically actuated, the reclosing lockout can be reset.

Cannot be combined with remote reset.Rated control voltage [Us]24 V DC VFor use withIZMX40...W

IZMX40...FDesign verification as per IEC/EN 61439

Operating ambient temperature min.-25 °COperating ambient temperature max.+70 °CTechnical data ETIM 7.0

Low-voltage industrial components (EG000017) / Shunt release (for power circuit breaker) (EC001023)Electric engineering,

automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Full load current trip ( [AKF016013])Rated control supply voltage Us at AC 50HZ0 - 0 VRated control supply voltage Us at AC 60HZ0 - 0 VRated control supply voltage Us at DC24 - 24 VVoltage type for actuatingDCInitial value of the undelayed short-circuit release - setting range0 AEnd value adjustment range undelayed short-circuit release0 AType of electric connectionFlat plug-in connectionNumber of contacts as normally...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-RR24DC-40-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.