


INDUSTRIAL COMPONENT DATA

IZMX-RR24DC-40-1 184125 68D2806G63 EATON ELECTRIC

184125 IZMX-RR24DC-40-1

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX-RR24DC-40-1



Manufacturer	EATON - MOELLER
MPN / Reference	IZMX-RR24DC-40-1
Catalog number	68D2806G63
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-C221D1BB49
Generated	2026-08-05

Product Overview

184125 IZMX-RR24DC-40-1

IZMX-RR24DC-40-1

Reset remote, 24VDC

Accessories, Remote reset, The circuit-breaker is equipped with a mechanical trip indicator (red pin)., After the remote reset coil is electrically actuated, the reclosing lockout can be reset., Cannot be combined with remote reset., Rated control voltage Us 24 V DC V, For use with IZMX40...W IZMX40...F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

Additional Product Information

EL-Nummer (Norway)0004398488Reset remote, 24VDCAccessories, Remote reset, The circuit-breaker is equipped with a mechanical trip indicator (red pin)., After the remote reset coil is electrically actuated, the reclosing lockout can be reset., Cannot be combined with remote reset., Rated control voltage Us 24 V DC V, For use with IZMX40...W IZMX40...FDelivery program

Product rangeAccessoriesAccessoriesTrip indication / Reset optionsAccessoriesRemote resetThe circuit-breaker is equipped with a mechanical trip indicator (red pin).

After the remote reset coil is electrically actuated, the reclosing lockout can be reset.

Cannot be combined with remote reset.Rated control voltage [Us]24 V DC VFor use withIZMX40...W

IZMX40...FInstructionsThe retrofit kit includes the required SEC control cable terminals.Design verification as per IEC/EN 61439

Operating ambient temperature min. -25 °C Operating ambient temperature max. +70 °C Technical data ETIM 7.0
Low-voltage industrial components (EG000017) / Shunt release (for power circuit breaker) (EC001023) Electric engineering,
automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Full load current trip
( [AKF016013]) Rated control supply voltage U_s at AC 50 Hz 0 - 0 V Rated control supply voltage U_s at AC
60 Hz 0 - 0 V Rated control supply voltage U_s at DC 24 - 24 V Voltage type for actuating DC Initial value of the undelayed
short-circuit release - setting range 0 A End value adjustment range undelay...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX-RR24DC-40-1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.