

INDUSTRIAL COMPONENT DATA

+IZMX-SH403-1 184188 Y7-184188 EATON ELECTRIC Shutter for withdrawable unit IZMX403. Can only be sold assemb..

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-SH403-1



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-SH403-1
Catalog number	Y7-184188
Category	Chassis part power circuit breaker
Minimum order	1 Pcs
Document ID	EO-55ABBE2827
Generated	2026-08-04

Product Overview

Shutter for withdrawable unit IZMX403. Can only be sold assembled.

+IZMX-SH403-1

Shutter for withdrawable unit IZMX403

Accessories, Shutter, When the breaker is withdrawn from its connected position, the shutters automatically cover the cassette's live main terminals., Installation type Withdrawable, Pole 3, For use with IZMX-CAS403..., for withdrawable unit

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

Additional Product Information

Shutter for withdrawable unit IZMX403Accessories, Shutter, When the breaker is withdrawn from its connected position, the shutters automatically cover the cassette's live main terminals., Installation type Withdrawable, Pole 3, For use with IZMX-CAS403..., for withdrawable unit

General specificationsProduct nameEaton Moeller series IZMX/INX shutterPart

no.+IZMX-SH403-1EAN4015081796809Product Length/Depth300 millimetreProduct height50 millimetreProduct width250 millimetreProduct weight0.625 kilogramCompliancesRoHS conformProduct TradenameIZMX/INXProduct

TypeAccessoriesProduct Sub TypeShutterDelivery programTypeAccessoryNumber of polesThree-poleNominal current4000

AFeaturesVersion as built-in deviceSpecial featuresFor withdrawable unit

When the breaker is withdrawn from its connected position, the shutters automatically cover the cassette's live main terminals.Used withIZMX-CAS403...

Three-poleTechnical Data - ElectricalElectrical connection type of main circuitOtherTechnical Data - MechanicalMounting

Method Withdrawable Design verification as per IEC/EN 61439 - technical data Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Additional information Accessory/spare part type Withdrawable units ETIM for 184188 Low-voltage industrial controls and switchgear (EC002043)

Feature Name

Feature Value

Rated current In (EF008250)

4000 A

Number of poles (EF001391)

3

Version as busbar adapter (EF006965)

No

Version as built-in device (EF006954)

Yes

Type of electrical c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-SH403-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.