

INDUSTRIAL COMPONENT DATA

+IZMX-ST110AD-1 184271 Y7-184271 EATON ELECTRIC Shunt release 110-125 VAC/DC. Can only be sold assembled.

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-ST110AD-1



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-ST110AD-1
Catalog number	Y7-184271
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-544E421A72
Generated	2026-08-05

Product Overview

Shunt release 110-125 VAC/DC. Can only be sold assembled.

+IZMX-ST110AD-1

Shunt release 110-125 VAC/DC

Accessories, Shunt release (for power circuit breaker), Can be combined with an undervoltage release or a second shunt release., Maximum operating frequency Actuations/minute 3, Limited to 3/min due to the high pick-up current for 35 ms., Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage U_s 110 - 127 V AC 50/60 Hz, 110 - 125 V DC V, Operating range x U_s 0,7 - 1,1 Factor, max. holding current I_n 0.071 A, max. pick-up current (35ms) I_n 5.54 A, max. continuous power AC/DC 10 VA/W, max. pull-in power (35ms) AC/DC 540 VA/W, Circuit-breaker total switching time @ $U_s=100\%$ 30 (IZMX16..., INX16...), 35 (IZMX40... , INX40...) ms, For use with IZMX16..., IZMX40..., INX16..., INX40...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers IZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series IZMX/INX - ACB Catalog Number 184271 Model Code +IZMX-ST110AD-1 EAN

4015081797011 Product Length/Depth 150 mm Product Height 100 mm Product Width 100 mm Product Weight 0.113 kg

Compliances RoHS conform Delivery program

Type Accessory Accessory/spare part type Remote switching Technical data - electrical

Voltage type AC/DC Control voltage operating range 110 - 127 V AC (50/60 Hz)

0.7 - 1.1 x U_s

110 - 125 V DC Rated control supply voltage (Us) at AC, 50 Hz - min 110 V Rated control supply voltage (Us) at AC, 50 Hz - max 127 V Rated control supply voltage (Us) at AC, 60 Hz - min 110 V Rated control supply voltage (Us) at AC, 60 Hz - max 127 V Rated control supply voltage (Us) at DC - min 110 V Rated control supply voltage (Us) at DC - max 125 V Current rating - max 0.071 A (maximum holding current) Rated operational current 0.071 A (maximum holding current) Starting current rating 5.54 A (35 ms) Adjustment range undelayed short-circuit release (end value) - max 0 A Power consumption 10 VA/W AC/DC Pick-up power consumption at 35 ms - max 540 VA/W Circuit breaker total switching time 30 ms (Us = 100%) (IZMX16..., INX16...) 35 ms (Us = 100%) (IZMX40..., INX40...) Initial value of the undelayed short-circuit release - min 0 A Technical data - mechanical Number of actuation per minute - max 3 Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 0 Design...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-ST110AD-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.