

INDUSTRIAL COMPONENT DATA

+IZMX-ST230AD-1 184273 Y7-184273 EATON ELECTRIC Shunt release 220-240 VAC/DC. Can only be sold assembled.

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-ST230AD-1



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-ST230AD-1
Catalog number	Y7-184273
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-41EDC8B822
Generated	2026-08-03

Product Overview

Shunt release 220-240 VAC/DC. Can only be sold assembled.

+IZMX-ST230AD-1

Shunt release 220-240 VAC/DC

Accessories, Shunt release (for power circuit breaker), Can be combined with an undervoltage release or a second shunt release., Maximum operating frequency Actuations/minute 3, Limited to 3/min due to the high pick-up current for 35 ms., Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage U_s 208 - 240 V AC 50/60 Hz, 208 - 250 V DC V, Operating range x U_s 0,7 - 1,1 Factor, max. holding current I_n 0.034 A, max. pick-up current (35ms) I_n 3.01 A, max. continuous power AC/DC 9 VA/W, max. pull-in power (35ms) AC/DC 500 VA/W, Circuit-breaker total switching time @ $U_s=100\%$ 30 (IZMX16..., INX16...), 35 (IZMX40... , INX40...) ms, For use with IZMX16..., IZMX40..., INX16..., INX40...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

Additional Product Information

Shunt release 220-240 VAC/DCAccessories, Shunt release (for power circuit breaker), Can be combined with an undervoltage release or a second shunt release., Maximum operating frequency Actuations/minute 3, Limited to 3/min due to the high pick-up current for 35 ms., Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage U_s 208 - 240 V AC 50/60 Hz, 208 - 250 V DC V, Operating range x U_s 0,7 - 1,1 Factor, max. holding current I_n 0.034 A, max. pick-up current (35ms) I_n 3.01 A, max. continuous power AC/DC 9 VA/W, max. pull-in power (35ms) AC/DC 500 VA/W, Circuit-breaker total switching time @ $U_s=100\%$ 30 (IZMX16..., INX16...), 35 (IZMX40... , INX40...) ms, For use with IZMX16..., IZMX40..., INX16..., INX40...

General specifications
Product name Eaton Moeller series IZMX/INX - ACB
Part no. +IZMX-ST230AD-1
EAN4015081797028
Product Length/Depth 150 millimetre
Product height 100 millimetre
Product width 100 millimetre
Product weight 0.113 kilogram
Compliance RoHS conform
Product Tradename IZMX/INX
Product Type ACB
Product Sub Type None
Delivery program Type Accessory
Special features Can be combined with an undervoltage release or a second shunt release.
Limited to 3/min due to the high pick-up current for 35 ms.
Please note - the circuit-breaker's switching frequency = 60/h
Suitable for Power circuit breaker
Off-load switch Used with INX16..., INX40...
IZMX16..., IZMX40...
Technical Data - Electrical
Voltage type AC/DC
Control voltage operating range 0.7 - 1.1 x U_s
208 - 250 V DC
208 - 240 V A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-ST230AD-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.