

INDUSTRIAL COMPONENT DATA

**+IZMX-ST48DC-1 184267 67C2820G54 EATON ELECTRIC
184267 +IZMX-ST48DC-1. Can only be sold assembled.**

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-ST48DC-1



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-ST48DC-1
Catalog number	67C2820G54
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-A47099AA6E
Generated	2026-08-02

Product Overview

184267 +IZMX-ST48DC-1. Can only be sold assembled.

+IZMX-ST48DC-1

Shunt release 48 VDC

Accessories, Shunt release (for power circuit breaker), Can be combined with an undervoltage release or a second shunt release., Maximum operating frequency Actuations/minute 3, Limited to 3/min due to the high pick-up current for 35 ms., Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage U_s 48 V DC V, Operating range x U_s 0,7 - 1,1 Factor, max. holding current I_n 0.089 A, max. pick-up current (35ms) I_n 10 A, max. continuous power AC/DC 5 VA/W, max. pull-in power (35ms) AC/DC 530 VA/W, Circuit-breaker total switching time @ $U_s=100\%$ 30 (IZMX16..., INX16...), 35 (IZMX40..., INX40...) ms, For use with IZMX16... , IZMX40..., INX16..., INX40...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers IZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series IZMX/INX shunt release Catalog Number 184267 Model Code +IZMX-ST48DC-1 EAN 4015081796991 Product Length/Depth 150 mm Product Height 100 mm Product Width 100 mm Product Weight 0.113 kg

Compliances RoHS conform Delivery program

Type Accessory Accessory/spare part type Remote switching Technical data - electrical

Voltage type DC Control voltage operating range 48 V DC

0.7 - 1.1 x U_s Rated control supply voltage (U_s) at AC, 50 Hz - min 0 V Rated control supply voltage (U_s) at AC, 50 Hz -

max 0 V Rated control supply voltage (Us) at AC, 60 Hz - min 0 V Rated control supply voltage (Us) at AC, 60 Hz - max 0 V
Rated control supply voltage (Us) at DC - min 48 V Rated control supply voltage (Us) at DC - max 48 V Current rating - max
0.089 A (maximum holding current) Rated operational current 0.089 A (maximum holding current) Starting current rating 10
A (35 ms) Adjustment range undelayed short-circuit release (end value) - max 0 A Power consumption 5 VA/W AC/DC
Pick-up power consumption at 35 ms - max 530 VA/W Circuit breaker total switching time 30 ms (Us = 100%) (IZMX16...,
INX16...)
35 ms (Us = 100%) (IZMX40..., INX40...) Initial value of the undelayed short-circuit release - min 0 A Technical data -
mechanical
Number of actuation per minute - max 3 Number of contacts (change-over contacts) 0 Number of contacts (normally closed
contacts) 0 Number of contacts (normally open contacts) 0 Design verification as per IEC/EN 61439 - techni...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-ST48DC-1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.