

INDUSTRIAL COMPONENT DATA

**+IZMX-STS230AD-1 184279 Y7-184279 EATON ELECTRIC
Shunt release (2) 220-240 VAC/DC. Can only be sold
assemble..**

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-STS230AD-1



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-STS230AD-1
Catalog number	Y7-184279
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-77D6AA1C57
Generated	2026-08-06

Product Overview

Shunt release (2) 220-240 VAC/DC. Can only be sold assembled.

+IZMX-STS230AD-1

Shunt release (2) 220-240 VAC/DC

Accessories, 2nd shunt release, Only in combination with a zfirstz shunt release., Cannot be combined with an undervoltage release., Maximum operating frequency Actuations/minute 3, Limited to 3/min due to the high pick-up current for 35 ms., Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage Us 208 - 240 V AC 50/60 Hz, 208 - 250 V DC V, Operating range x US 0,7 - 1,1 Factor, max. holding current In 0.034 A, max. continuous power AC/DC 9 VA/W, Circuit-breaker total switching time @ US=100% 30 (IZMX16..., INX16...), 35 (IZMX40..., INX40...) ms, For use with IZMX16..., IZMX40..., INX16..., INX40...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers IZM
--------------	--

Additional Product Information

Shunt release (2) 220-240 VAC/DCAccessories, 2nd shunt release, Only in combination with a "first" shunt release., Cannot be combined with an undervoltage release., Maximum operating frequency Actuations/minute 3, Limited to 3/min due to the high pick-up current for 35 ms., Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage Us 208 - 240 V AC 50/60 Hz, 208 - 250 V DC V, Operating range x US 0,7 - 1,1 Factor, max. holding current In 0.034 A, max. continuous power AC/DC 9 VA/W, Circuit-breaker total switching time @ US=100% 30 (IZMX16..., INX16...), 35

(IZMX40..., INX40...) ms, For use with IZMX16..., IZMX40..., INX16..., INX40...

General specificationsProduct nameEaton Moeller series IZMX/INX shunt releasePart

no.+IZMX-STS230AD-1EAN4015081797073Product Length/Depth150 millimetreProduct height100 millimetreProduct

width100 millimetreProduct weight0.113 kilogramCompliancesRoHS conformProduct TradenameIZMX/INXProduct

TypeAccessoriesProduct Sub TypeShunt releaseDelivery programTypeAccessorySpecial featuresLimited to 3/min due to the high pick-up current for 35 ms.

Please note - the circuit-breaker's switching frequency = 60/h

Only in combination with a ""first"" shunt release.

Cannot be combined with an undervoltage release."Suitable forPower circuit breaker

Off-load switchUsed withINX16..., INX40...

IZMX16..., IZMX40...Technical Data - ElectricalVoltage typeAC/DCControl voltage operating range0.7 - 1.1 x Us

208 - 240 V AC (50/60 Hz)

208 - 250 V DCRated....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-STS230AD-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.