

INDUSTRIAL COMPONENT DATA

+IZMX-STS48DC-1 184276 Y7-184276 EATON ELECTRIC Shunt release (2) 48 VDC. Can only be sold assembled.

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-STS48DC-1



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-STS48DC-1
Catalog number	Y7-184276
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-055D54D859
Generated	2026-08-02

Product Overview

Shunt release (2) 48 VDC. Can only be sold assembled.

+IZMX-STS48DC-1

Shunt release (2) 48 VDC

Accessories, 2nd shunt release, Only in combination with a zfirstz shunt release., Cannot be combined with an undervoltage release., Maximum operating frequency Actuations/minute 3, Limited to 3/min due to the high pick-up current for 35 ms., Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage U_s 48 V DC V, Operating range x U_s 0,7 - 1,1 Factor, max. holding current I_n 0.189 A, max. pick-up current (35ms) I_n 10 A, max. continuous power AC/DC 5 VA/W, max. pull-in power (35ms) AC/DC 530 VA/W, Circuit-breaker total switching time @ $U_s=100\%$ 30 (IZMX16..., INX16...), 35 (IZMX40..., INX40...) ms, For use with IZMX16... , IZMX40..., INX16..., INX40...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers IZM
--------------	--

Additional Product Information

Shunt release (2) 48 VDCAccessories, 2nd shunt release, Only in combination with a "first" shunt release., Cannot be combined with an undervoltage release., Maximum operating frequency Actuations/minute 3, Limited to 3/min due to the high pick-up current for 35 ms., Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage U_s 48 V DC V, Operating range x U_s 0,7 - 1,1 Factor, max. holding current I_n 0.189 A, max. pick-up current (35ms) I_n 10 A, max. continuous power AC/DC 5 VA/W, max. pull-in power (35ms) AC/DC 530 VA/W, Circuit-breaker total switching time @ $U_s=100\%$ 30 (IZMX16..., INX16...), 35 (IZMX40..., INX40...) ms, For use with IZMX16... , IZMX40..., INX16..., INX40...
General specificationsProduct nameEaton Moeller series IZMX/INX shunt releasePart

no.+IZMX-STS48DC-1EAN4015081797042Product Length/Depth150 millimetreProduct height100 millimetreProduct width100 millimetreProduct weight0.113 kilogramCompliancesRoHS conformProduct TradenameIZMX/INXProduct TypeAccessoriesProduct Sub TypeShunt releaseDelivery programTypeAccessorySpecial featuresLimited to 3/min due to the high pick-up current for 35 ms.

Please note - the circuit-breaker's switching frequency = 60/h

Only in combination with a ""first"" shunt release.

Cannot be combined with an undervoltage release."Suitable forOff-load switch

Power circuit breakerUsed withINX16..., INX40...

IZMX16..., IZMX40...Technical Data - ElectricalVoltage typeDCControl voltage operating range48 V DC

0.7 - 1.1 x UsRat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-STS48DC-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.