

INDUSTRIAL COMPONENT DATA

IZMX-TF403-3200F-1 184176 Y7-184176 EATON ELECTRIC Connections, front, 3200A, IZMX40, 3 p, fixed mounted des..

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX-TF403-3200F-1



Manufacturer	EATON - MOELLER
MPN / Reference	IZMX-TF403-3200F-1
Catalog number	Y7-184176
Category	Connection vane/phase spreader
Minimum order	1 Pcs
Document ID	EO-961FD8D868
Generated	2026-08-05

Product Overview

Connections, front, 3200A, IZMX40, 3 p, fixed mounted design
IZMX-TF403-3200F-1

Accessories, Front connections, This connection kit comes with front terminals for connection to the circuit-breaker. The circuit-breaker can be connected directly with CU bars on the rear flanged connection. If necessary, the optional front terminals can be installed before the circuit-breaker is installed in the enclosure. This way, the final connection to the circuit-breaker can be made from the front., Installation type Fixed, Rated current In 3200 A, Pole 3, For use with IZMX40...3...32F, INX40...3...32F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers IZM
--------------	--

Additional Product Information

EL-Nummer (Norway)0004398519Connections, front, 3200A, IZMX40, 3 p, fixed mounted designAccessories, Front connections, This connection kit comes with front terminals for connection to the circuit-breaker. The circuit-breaker can be connected directly with CU bars on the rear flanged connection. If necessary, the optional front terminals can be installed before the circuit-breaker is installed in the enclosure. This way, the final connection to the circuit-breaker can be made from the front., Installation type Fixed, Rated current In 3200 A, Pole 3, For use with IZMX40...3...32F, INX40...3...32FDelivery program

Product rangeAccessoriesAccessoriesMain terminal kitsAccessoriesFront connectionsThis connection kit comes with front terminals for connection to the circuit-breaker. The circuit-breaker can be connected directly with CU bars on the rear flanged connection. If necessary, the optional front terminals can be installed before the circuit-breaker is installed in the

enclosure. This way, the final connection to the circuit-breaker can be made from the front. Rated current [In] 3200

APole3For use with IZMX40...3...32F

INX40...3...32F Information about equipment supplied Each set includes the connections for top and bottom. 3-pole for 6 connections, 4-pole for 8 connections

Screws, washers, and supports are included as standard. Installation type Fixed Design verification as per IEC/EN 61439

Operating ambient temperature min. -25 °C Operating ambient temperature max. +70 °C Technical data ETIM 7.0

Low...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX-TF403-3200F-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.