

INDUSTRIAL COMPONENT DATA

+IZMX-UVR110AD-1 184113 Y7-184113 EATON ELECTRIC
Undervoltage release 110-125 VAC/DC. Can only be sold
assem..

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-UVR110AD-1



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-UVR110AD-1
Catalog number	Y7-184113
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-CE0ED2CADF
Generated	2026-08-02

Product Overview

Undervoltage release 110-125 VAC/DC. Can only be sold assembled.

+IZMX-UVR110AD-1

Undervoltage release 110-125 VAC/DC

Accessories, Undervoltage release, Cannot be combined with a second shunt release., Maximum operating frequency Actuations/minute 3, Limited to 3/min due to the high pick-up current for 35 ms., Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage U_s 110 - 127 V AC 50/60 Hz, 110 - 125 V DC V, Operating range x US 0,85 - 1,1 Factor, max. holding current I_n 0.056 A, max. pick-up current (35ms) I_n 8.04 A, max. continuous power AC/DC 5 VA/W, max. pull-in power (35ms) AC/DC 890 VA/W, Circuit-breaker total switching time @ $U_s=100\%$ 37 ms, For use with IZMX16..., IZMX40..., INX16..., INX40...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers IZM
--------------	--

Additional Product Information

Undervoltage release 110-125 VAC/DCAccessories, Undervoltage release, Cannot be combined with a second shunt release., Maximum operating frequency Actuations/minute 3, Limited to 3/min due to the high pick-up current for 35 ms., Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage U_s 110 - 127 V AC 50/60 Hz, 110 - 125 V DC V, Operating range x US 0,85 - 1,1 Factor, max. holding current I_n 0.056 A, max. pick-up current (35ms) I_n 8.04 A, max. continuous power AC/DC 5 VA/W, max. pull-in power (35ms) AC/DC 890 VA/W, Circuit-breaker total switching time @

US=100% 37 ms, For use with IZMX16..., IZMX40..., INX16..., INX40...

General specifications Product name Eaton Moeller series IZMX/INX undervoltage release Part no. +IZMX-UVR110AD-1 EAN4015081796472 Product Length/Depth 150 millimetre Product height 100 millimetre Product width 100 millimetre Product weight 0.091 kilogram Compliances RoHS conform Product Tradename IZMX/INX Product Type Accessories Product Sub Type Undervoltage release Delivery program Type Accessory Special features Cannot be combined with a second shunt release.

Limited to 3/min due to the high pick-up current for 35 ms.

Please note - the circuit-breaker's switching frequency = 60/h Suitable for Off-load switch

Power circuit breaker Used with IZMX16..., IZMX40...

INX16..., INX40... Technical Data - Electrical Voltage type AC/DC Control voltage operating range 110 - 125 V DC

110 - 127 V AC (50/60 Hz)

0.85 - 1.1 x Us Rated control supply voltage (Us) at AC, 50 Hz -....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-UVR110AD-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.