

**INDUSTRIAL COMPONENT DATA**

# IZMX16H3-V08W-1 183352 Y7-183352 EATON ELECTRIC

## Circuit-breaker, 3 pole, 800 A, 66 kA, Selective operation, ..

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX16H3-V08W-1



|                 |                                                                   |
|-----------------|-------------------------------------------------------------------|
| Manufacturer    | EATON - MOELLER                                                   |
| MPN / Reference | IZMX16H3-V08W-1                                                   |
| Catalog number  | Y7-183352                                                         |
| Category        | Power circuit-breaker for trafo/generator/installation protection |
| Minimum order   | 1 Pcs                                                             |
| Document ID     | EO-C8F75E95BC                                                     |
| Generated       | 2026-08-05                                                        |

### Product Overview

Circuit-breaker, 3 pole, 800 A, 66 kA, Selective operation, IEC, Withdrawable

IZMX16H3-V08W-1

Eaton Moeller series IZMX/INX - ACB. IZMX16, 3p, 800 A, Icu (

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers IZM**

### Additional Product Information

General specifications

Product Name Eaton Moeller series IZMX/INX circuit-breaker Catalog Number 183352 Model Code IZMX16H3-V08W-1

EAN 4015081789405 Product Length/Depth 584 mm Product Height 597 mm Product Width 521 mm Product Weight 27.74 kg

Compliances IEC

IEC/EN 60947

RoHS conform

ETIM for 183352 Low-voltage industrial controls and switchgear (EC000228)

Feature Name

Feature Value

Rated permanent current Iu (EF001389)

800 A

Rated voltage (EF003977)

690 V

Rated short-circuit breaking capacity Icu at 400 V, 50 Hz (EF007048)  
65 kA  
Overload release current setting (EF002336)  
320 A  
Adjustment range short-term delayed short-circuit release (EF007129)  
480 A  
Adjustment range undelayed short-circuit release (EF007131)  
1600 A  
Power loss (EF005387)  
80 W  
Device construction (EF008240)  
Built-in device slide-in technique (withdrawable)  
Integrated earth fault protection (EF007296)  
No  
Type of electrical connection of main circuit (EF006819)  
Rail connection  
Suitable for DIN rail (top hat rail) mounting (EF007250)  
No  
DIN rail (top hat rail) mounting optional (EF008904)  
No  
Number of auxiliary contacts as normally closed contact (EF001377)  
0  
Number of auxiliary contacts as normally open contact (EF001376)  
0  
Number of auxiliary contacts as change-over contact (EF003531)  
2  
With switched-off indicator (EF007006)  
Yes  
With integrated under voltage release (EF001390)  
No  
Number of poles (EF001391)  
3  
Position of connection for main current circuit (EF006671)  
Back  
Type of control element (EF006976)  
P...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX16H3-V08W-1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.