

INDUSTRIAL COMPONENT DATA

IZMX40B3-V32W-1 183732 Y7-183732 EATON ELECTRIC Circuit-breaker, 3 pole, 3200 A, 66 kA, Selective operation,..

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX40B3-V32W-1



Manufacturer	EATON - MOELLER
MPN / Reference	IZMX40B3-V32W-1
Catalog number	Y7-183732
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-6EF2AA5114
Generated	2026-08-05

Product Overview

Circuit-breaker, 3 pole, 3200 A, 66 kA, Selective operation, IEC, Withdrawable
IZMX40B3-V32W-1

Eaton Moeller series IZMX/INX - ACB. Circuit-breaker, 3p, 3200A, 66 kA, Selective operation, IEC, Withdrawable
Circuit-breaker IZMX40 (Air circuit-breakers/switch-disconnectors), 3 pole, Current Range: Up to 4000 A, Rated current =
rated uninterrupted current($I_n = I_u$): 3200 A, up to 440 V 50/60 Hz(I_{cu}): 66 kA, up to 440 V 50/60 Hz(I_{cs}): 66 kA, Overload
release, min.(I_r): 1280 A, Overload release, max.(I_r): 3200 A, Installation type: Withdrawable, Standard/Approval: IEC,
Protective function: Selective operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers IZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series IZMX/INX circuit-breaker Catalog Number 183732 Model Code IZMX40B3-V32W-1
EAN 4015081794683 Product Length/Depth 584 mm Product Height 597 mm Product Width 521 mm Product Weight 69 kg
Compliances IEC

IEC/EN 60947

RoHS conform Delivery program

Type Frame IZMX40 Number of poles Three-pole Amperage Rating 3200 A Release system Electronic release Technical
data - electrical

Voltage rating at AC 690 V AC Rated operating voltage (Ue) - min 690 V Rated operating voltage (Ue) - max 690 V Rated

insulation voltage (Ui) 1000 V Rated impulse withstand voltage (Uimp) 12 kV AC Rated uninterrupted current (Iu) 3200 A
Rated uninterrupted current (Iu) at 50°C 3200 A Rated uninterrupted current (Iu) at 60°C 3200 A Rated uninterrupted
current (Iu) at 70°C 3200 A Rated short-time withstand current (t = 1 s) 66 kA Rated short-time withstand current at 50/60
Hz (t = 3 s) 53 kA Overload release current setting - min 1280 A Overload release current setting - max 3200 A Short-circuit
release delayed setting - min 2400 A Short-circuit release delayed setting - max 32000 A Short-circuit release non-delayed
setting 1.5 - 10 x Ir Short-circuit release non-delayed setting - min 0 A Short-circuit release non-delayed setting - max 48000
A Adjustment range short-term delayed short-circuit release - min 1920 A Adjustment range short-term delayed short-circuit
release - max 32000 A Adjustment range undelayed short-circuit release - min 6400 A Adjustment...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX40B3-V32W-1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.