

INDUSTRIAL COMPONENT DATA

IZMX40H3-V25W-1 183747 Y7-183747 EATON ELECTRIC

Circuit-breaker, 3 pole, 2500 A, 105 kA, Selective operation..

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX40H3-V25W-1



Manufacturer	EATON - MOELLER
MPN / Reference	IZMX40H3-V25W-1
Catalog number	Y7-183747
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-40127195C1
Generated	2026-08-05

Product Overview

Circuit-breaker, 3 pole, 2500 A, 105 kA, Selective operation, IEC, Withdrawable

IZMX40H3-V25W-1

Circuit-breaker IZMX40 (Air circuit-breakers/switch-disconnectors), 3 pole, Current Range: Up to 4000 A, Rated current = rated uninterrupted current(In = Iu): 2500 A, up to 440 V 50/60 Hz(Icu): 105 kA, up to 440 V 50/60 Hz(Ics): 105 kA, Overload release, min.(Ir): 1000 A, Overload release, max.(Ir): 2500 A, Installation type: Withdrawable, Standard/Approval: IEC, Protective function: Selective operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers IZM
--------------	--

Additional Product Information

Circuit-breaker, 3 pole, 2500A, 105 kA, Selective operation, IEC, WithdrawableCircuit-breaker IZMX40 (Air circuit-breakers/switch-disconnectors), 3 pole, Current Range: Up to 4000 A, Rated current = rated uninterrupted current(In = Iu): 2500 A, up to 440 V 50/60 Hz(Icu): 105 kA, up to 440 V 50/60 Hz(Ics): 105 kA, Overload release, min.(Ir): 1000 A, Overload release, max.(Ir): 2500 A, Installation type: Withdrawable, Standard/Approval: IEC, Protective function: Selective operation

General specificationsProduct nameEaton Moeller series IZMX/INX circuit-breakerPart

no.IZMX40H3-V25W-1EAN4015081794836Product Length/Depth584 millimetreProduct height597 millimetreProduct width521 millimetreProduct weight69 kilogramCompliancesIEC/EN 60947

IEC

RoHS conformProduct TradenameIZMX/INXProduct TypeCircuit-breakerProduct Sub TypeNoneDelivery programTypeAir

circuit breakers/switch-disconnector

Open circuit breakerNumber of polesThree-poleAmperage Rating2500 ARelease systemElectronic

releaseFeaturesComplete device with protection unit

Motor drive optionalSpecial featuresCassette must be separately ordered.

Main terminals must be separately ordered.

suitable for zone selectivity

optionally fittable by user with comprehensive accessories

Terminal capacity hint: These are values used in separate switchgear. The actual values will depend on the temperature around the circuit breaker, which is influenced by the ambient temperature, the degree of protection (IP), the mounting height, the part...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX40H3-V25W-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.