

INDUSTRIAL COMPONENT DATA

Q18S1R-A1 072312 Y7-72312 EATON ELECTRIC Key-operated actuator, 2 positions, black, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: Q18S1R-A1



Manufacturer	EATON - MOELLER
MPN / Reference	Q18S1R-A1
Catalog number	Y7-72312
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-A6918A8567
Generated	2026-08-04

Product Overview

Key-operated actuator, 2 positions, black, maintained

Key selector. 16 mm. 18x18 mm. Interlocking. 2 positions. Black

Eaton Moeller® series RMQ16 Key-operated actuator, 2 positions, black, maintained Q18S1R-A1

Key-operated actuator, Product range: RMQ16, Single unit, Design: Key operated, maintained, 2 positions, Degree of Protection: IP65, without bezel, Connection to SmartWire-DT: no, Front dimensions: Front dimensions 18 × 18 mm, With 1 key, For each color there is a corresponding key, -> accessories,, Degree of Protection: IP65

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series RMQ16 Key-operated actuator Catalog Number 072312 Model Code Q18S1R-A1
EAN 4015080723127 Product Length/Depth 50 mm Product Height 18 mm Product Width 18 mm Product Weight 0.02 kg
Certifications CSA Class No.: 3211-03

CSA

UL

CE

CSA File No.: 46552

CSA-C22.2 No. 14-05

IEC/EN 60947

UL 508

UL Category Control No.: NKCR

IEC/EN 60947-5

UL File No.: E29184 Features & Functions

Bezel color Black Bezel material Plastic Design Key operated Fitted with: Front ring General

Accessories 1 key included with supplied equipment. Degree of protection NEMA 1 Degree of protection (front side) IP65

Lifespan, mechanical 3,000,000 Operations Opening diameter 16 mm Operating frequency 1800 Operations/h Operating

torque 0.4 Nm Overvoltage category III Pollution degree 3 Product category RMQ16 Rated impulse withstand voltage

(Uimp) 800 V AC Size Front dimensions: 18 x 18 mm Switching angle 45 ° Terminal capacity 0.5 - 1.0 mm² Terminal size

2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors

2.8 x 0.8 mm to DIN 46244, Blade terminal Type Key-operated button Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature

(enclosed) - min -25 °C Ambient operating....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q18S1R-A1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.