

## INDUSTRIAL COMPONENT DATA

# M22-WRS-MS7 111788 Y7-111788 EATON ELECTRIC

## Key-operated actuator, 2 positions, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: M22-WRS-MS7



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | EATON - MOELLER                   |
| MPN / Reference | M22-WRS-MS7                       |
| Catalog number  | Y7-111788                         |
| Category        | Front element for selector switch |
| Minimum order   | 1 Pcs                             |
| Document ID     | EO-9F9EE8C292                     |
| Generated       | 2026-08-03                        |

### Product Overview

Key-operated actuator, 2 positions, maintained

M22-WRS-MS7

Eaton Moeller® series M22 Key-operated actuator, maintained, 2 positions, MS7, Key withdrawable: 0, I, Bezel: titanium  
Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: Key operated, maintained, Not suitable for master key systems, 2 positions, Lock mechanism: MS7, I, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Key withdraw convertible with coding adapters M22-XC-..., With 1 key, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

### Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Key-operated actuator Catalog Number 111788 Model Code M22-WRS-MS7  
EAN 4015081113385 Product Length/Depth 70 mm Product Height 30 mm Product Width 30 mm Product Weight 0.034 kg  
Compliances CE Marked Certifications UL 508  
EN 60947-5  
CSA Std. C22.2 No. 94-91  
CSA Std. C22.2 No. 14-05  
IEC 60947-5

VDE

CSA

CSA-C22.2 No. 94-91

IEC/EN 60947-5

UL

UL Category Control No.: NKCR

VDE 0660

CSA File No.: 012528

CE

CSA-C22.2 No. 14-05

CSA Class No.: 3211-03

UL File No.: E29184

IEC/EN 60947

DNV

GL

LR Features & Functions

Bezel color Titanium Bezel material Plastic Color Black Design Key operated

Classical Fitted with: Front ring Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y Key code MS7 General

Accessories 1 key included with supplied equipment. Degree of protection NEMA 4X, 13 Degree of protection (front side)

IP66 Lifespan, mechanical 100,000 Operations Opening diameter 22.5 mm Operating frequency 100 Operations/h

Operating torque 0.5 Nm Overvoltage category III Pollution degree 3 Product category RMQ-Titan Size Front diameter: 29.7 mm Switching angle 60 ° Type Key-operated button Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Cl...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-WRS-MS7 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.