

INDUSTRIAL COMPONENT DATA

M22-WRS-SA(*)-* 216892 Y7-216892 EATON ELECTRIC

Key-operated actuator, 2 positions, maintained type accordin..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-WRS-SA(*)-*



Manufacturer	EATON - MOELLER
MPN / Reference	M22-WRS-SA(*)-*
Catalog number	Y7-216892
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-CE7AEC09CE
Generated	2026-08-04

Product Overview

Key-operated actuator, 2 positions, maintained type according to data

M22-WRS-SA(*)-*

Key-operated actuator, maintained, 2 positions 0, Bezel: titanium, Suitable for master key systems

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Key-operated actuator, maintained, 2 positions 0, Bezel: titanium, Suitable for master key systemsKey-operated actuator, Product range: RMQ-Titan, Single unit, Design: Key operated, maintained, Suitable for master key systems, 2 positions, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, with two keys, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66

General specificationsProduct nameEaton Moeller® series M22 Key-operated actuatorPart no.M22-WRS-SA(*)-*Product Length/Depth70 millimetreProduct height30 millimetreProduct width30 millimetreProduct weight0.034

kilogramCompliancesCE MarkedCertificationsCSA Std. C22.2 No. 94-91

UL 508

EN 60947-5

IEC 60947-5

CSA Std. C22.2 No. 14-05

VDE

CE

CSA-C22.2 No. 14-05

UL File No.: E29184

CSA File No.: 012528

UL Category Control No.: NKCR

CSA-C22.2 No. 94-91

VDE 0660

IEC/EN 60947-5

IEC/EN 60947

UL

CSA

CSA Class No.: 3211-03Product TradenameM22Product TypeKey-operated actuatorProduct Sub TypeNoneFeatures & FunctionsBezel colorTitaniumBezel materialPlasticDesignKey operatedFitted with:Front ringGeneral informationAccessories2 keys included with supplied equipment.Degree of protectionNEMA 4X, 13Degree of protection (front side)IP66Lifespan, mechanical100,000 OperationsOpening diameter22.5 mmOperating frequency100 Operations/hOperating torque0.5 N·mProduct categoryRMQ-TitanSizeFront diameter: 29.7 mmSuitable forMaster key systemsSwitching angle60 °TypeKey...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-WRS-SA(*)-* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.