

INDUSTRIAL COMPONENT DATA

M22S-WRS-SA(*)-* 216893 Y7-216893 EATON ELECTRIC

Key-operated actuator, 2 positions, maintained type accordi..

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-WRS-SA(*)-*



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-WRS-SA(*)-*
Catalog number	Y7-216893
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-5A89F638E8
Generated	2026-08-04

Product Overview

Key-operated actuator, 2 positions, maintained type according to data

M22S-WRS-SA(*)-*

Key-operated actuator, maintained, 2 positions 0, Bezel: black, Suitable for master key systems

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Key-operated actuator, maintained, 2 positions 0, Bezel: black, Suitable for master key systemsKey-operated actuator, Product range: RMQ-Titan, Single unit, Design: Key operated, maintained, Suitable for master key systems, 2 positions, Degree of Protection: IP66, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, with two keys, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66

General specificationsProduct nameEaton Moeller® series M22 Key-operated actuatorPart no.M22S-WRS-SA(*)-*Product Length/Depth70 millimetreProduct height30 millimetreProduct width30 millimetreProduct weight0.034 kilogramCertificationsIEC/EN 60947-5

CE

UL 508

CSA-C22.2 No. 14-05

CSA Class No.: 3211-03

CSA

UL Category Control No.: NKCR

UL
VDE 0660
UL File No.: E29184
IEC/EN 60947
CSA-C22.2 No. 94-91
CSA File No.: 012528
Product Tradename M22
Product Type Key-operated actuator
Product Sub Type None
Features & Functions Bezel color Black
Bezel material Plastic
Design Key operated
Fitted with: Front ring
General information Accessories 2 keys included with supplied equipment.
Degree of protection NEMA 4X, 13
Degree of protection (front side) IP66
Lifespan, mechanical 100,000 Operations
Opening diameter 22.5 mm
Operating frequency 100 Operations/h
Operating torque 0.5 N·m
Product category RMQ-Titan
Size Front diameter: 29.7 mm
Suitable for Master key systems
Switching angle 60°
Type Key-operated button
Ambient conditions, mechanical
Mounting position As required
Shock resistance Mechanical, Acc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-WRS-SA(*)-* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.