

INDUSTRIAL COMPONENT DATA

M22S-WS-MS* 216884 Y7-216884 EATON ELECTRIC

Key-operated actuator, 2 positions, momentary, closure according..

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-WS-MS*



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-WS-MS*
Catalog number	Y7-216884
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-D0CA52C8A1
Generated	2026-08-04

Product Overview

Key-operated actuator, 2 positions, momentary, closure according to data

M22S-WS-MS*

Eaton Moeller® series M22 Key-operated actuator, momentary, 2 positions, MS1-MS20, Key withdrawable: 0, Bezel: black
Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: Key operated, momentary, Not suitable for master key systems, 2 positions, Lock mechanism: selectable, Degree of Protection: IP66, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, Instructions: Stay-put/spring-return function, can be changed with coding parts M22-XC-Y, Key withdraw convertible with coding adapters M22-XC-..., With 1 key, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Key-operated actuator Catalog Number 216884 Model Code M22S-WS-MS*

Product Length/Depth 70 mm Product Height 30 mm Product Width 30 mm Product Weight 0.034 kg Certifications CE IEC/EN 60947

UL Category Control No.: NKCR

CSA-C22.2 No. 14-05

UL

CSA-C22.2 No. 94-91

IEC/EN 60947-5

CSA File No.: 012528

UL 508

VDE 0660

CSA Class No.: 3211-03

CSA

UL File No.: E29184

DNV

GL

LR Features & Functions

Bezel color Black Bezel material Plastic Design Key operated

Classical Fitted with: Front ring Functions Stay-put/spring-return function, can be changed with coding parts M22-XC-Y Key code Selectable General

Accessories 1 key included with supplied equipment. Degree of protection NEMA 4X, 13 Degree of protection (front side)

IP66 Lifespan, mechanical 100,000 Operations Opening diameter 22.5 mm Operating frequency 100 Operations/h

Operating torque 0.5 Nm Overvoltage category III Pollution degree 3 Product category RMQ-Titan Size Front diameter: 29.7 mm Switching angle 40 ° Type Key-operated button Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Communication

Connection to Smart...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-WS-MS* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.