

INDUSTRIAL COMPONENT DATA

Q18S3R-A4 072318 EATON ELECTRIC Key-operated actuator, 3 positions, black, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: Q18S3R-A4



Manufacturer	EATON - MOELLER
MPN / Reference	Q18S3R-A4
Catalog number	072318
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-18AF99BDD3
Generated	2026-08-04

Product Overview

Key-operated actuator, 3 positions, black, maintained

Key selector. 16 mm. 18x18 mm. Interlocking. 3 positions. Black

Key-operated actuator, Product range: RMQ16, Single unit, Design: Key operated, maintained/momentary, 3 positions, I, Degree of Protection: IP65, without bezel, Connection to SmartWire-DT: no, Front dimensions: Front dimensions 18 × 18 mm, With 1 key, Degree of Protection: IP65

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Key-operated actuator, 3 positions, black, maintained Key-operated actuator, Product range: RMQ16, Single unit, Design: Key operated, maintained/momentary, 3 positions, I, Degree of Protection: IP65, without bezel, Connection to SmartWire-DT: no, Front dimensions: Front dimensions 18 × 18 mm, With 1 key, Degree of Protection: IP65 Delivery program

Product range RMQ16 Basic function Key-operated buttons Single unit/Complete unit Single unit Design Key operated maintained/momentary Function: [= spring-return] 45°45° 3 positions Key withdrawable in position I 0 Degree of Protection IP65 Front ring without bezel Connection to SmartWire-DT no Front dimensions Front dimensions 18 × 18 mm Information about equipment supplied With 1 key Technical data

General Standards IEC/EN 60947 Lifespan, mechanical [Operations] > 3 × 10⁶ Operating frequency [Operations/h] ? 1800 Operating torque ? 0.4 Nm Degree of protection, IEC/EN 60529 IP65 Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open -25 - +60 °C Ambient temperature Enclosed - 25 - 40 °C

Mounting position As required Mechanical shock resistance > 40

according to IEC 60068-2-27

Shock duration 11 ms

Sinusoidal g Terminal capacities 0.5 - 1.0 mm² Blade terminal 2.8 x 0.8 mm to DIN 46244 Fast-on connectors 2.8 x 0.8 mm to DIN 46247 and IEC 60760 Contacts Rated impulse withstand voltage [U_{imp}] 800 V AC Rated insulation voltage [U_i] 250 V Overvoltage category/pollution degree....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Q18S3R-A4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.