

INDUSTRIAL COMPONENT DATA

M22S-WRS3-SA(*)-* 216906 Y7-216906 EATON ELECTRIC

Key-operated actuator, 3 positions, maintained, type accor..

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-WRS3-SA(*)-*



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-WRS3-SA(*)-*
Catalog number	Y7-216906
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-D5A40E05C8
Generated	2026-08-04

Product Overview

Key-operated actuator, 3 positions, maintained, type according to data

M22S-WRS3-SA(*)-*

Key-operated actuator, maintained, 3 positions 0, Bezel: black, Suitable for master key systems

Key-operated actuator, Product range: RMQ-Titan, Single unit, Design: Key operated, maintained, Suitable for master key systems, 3 positions, Degree of Protection: IP66, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, with two keys, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Key-operated actuator, maintained, 3 positions 0, Bezel: black, Suitable for master key systemsKey-operated actuator, Product range: RMQ-Titan, Single unit, Design: Key operated, maintained, Suitable for master key systems, 3 positions, Degree of Protection: IP66, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 29,7, with two keys, Standards: IEC/EN 60947, VDE 0660, Degree of Protection: IP66Delivery program Product rangeRMQ-TitanBasic functionKey-operated buttonsMounting hole diameter [?]22.5 mmSingle unit/Complete unitSingle unitDesignKey operatedmaintainedFunction: [= spring-return]60° ? 60°Suitable for master key systems3 positionsKey withdrawable in position0Degree of ProtectionIP66Front ringBezel: blackConnection to SmartWire-DTyes with SWD-RMQ connectionsInformation about equipment suppliedwith two keysTechnical data GeneralStandardsIEC/EN 60947 VDE 0660Lifespan, mechanical [Operations]> 0.1 x 106Operating frequency [Operations/h]? 100Ordering information for

users? 0.5 NmClimatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Degree of ProtectionIP66Ambient temperatureOpen-25 - +70 °CMounting positionAs requiredMechanical shock resistance30

Shock duration 11 ms

Sinusoidal

according to IEC 60068-2-27 gshipping classificationDNV

GL

LRDesign verification as per IEC/EN 61439

Technical data for design verificationRated operational current for specified heat dissipation [In]0 AHeat dissipation p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-WRS3-SA(*)-* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.