


INDUSTRIAL COMPONENT DATA

M22-T-DD 216396 Y7-216396 EATON ELECTRIC

Key-protection diaphragm, for double actuator pushbutton

Brand: EATON - MOELLER | Manufacturer Part Number: M22-T-DD



Manufacturer	EATON - MOELLER
MPN / Reference	M22-T-DD
Catalog number	Y7-216396
Category	Protective cover for command devices
Minimum order	1 Pcs
Document ID	EO-8F24D85B9B
Generated	2026-08-05

Product Overview

Key-protection diaphragm, for double actuator pushbutton

M22-T-DD

Eaton Moeller® series M22 Double actuator pushbutton

Double actuator pushbutton, For use with: M22(N/O)-DDL..., transparent version for harsh environmental conditions and application in the food industry, Do not use in conjunction with M22S-ST legend plate mount, since degree of protection cannot be guaranteed, additional protection for double actuator pushbuttons, Silicone

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Double actuator pushbutton Catalog Number 216396 Model Code M22-T-DD EAN 4015082163969 Product Length/Depth 33 mm Product Height 23 mm Product Width 58 mm Product Weight 0.008 kg Certifications CE Features & Functions

Color Colorless Features Transparent Material Silicone Shape Round General

Degree of protection NEMA 13

NEMA 12

NEMA 3R

NEMA 4X Model Other Protection Additional protection for double actuator pushbuttons Used with Double actuator pushbuttons Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication
Connection to SmartWire-DT No Contacts
Force for positive opening - min 0 N Design verification
Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,
current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation,
non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1
Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance
of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal
heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation
Please en...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-T-DD with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.