

INDUSTRIAL COMPONENT DATA

PKZM0-XDM12 283149 Y7-283149 EATON ELECTRIC Kit, +component adapter, for DOL starter for DILM7-M15

Brand: EATON - MOELLER | Manufacturer Part Number: PKZM0-XDM12



Manufacturer	EATON - MOELLER
MPN / Reference	PKZM0-XDM12
Catalog number	Y7-283149
Category	Wiring set for power circuit breaker
Minimum order	1 Pcs
Document ID	EO-EED95B3771
Generated	2026-08-05

Product Overview

Kit, +component adapter, for DOL starter for DILM7-M15

PKZM0-XDM12

Eaton Moeller® series PKZM0 Wiring set, For DOL Starter, DILM7-M15

Wiring set can be used for DOL starter for PKZM0 + DILM7, PKZM0 + DILM9, PKZM0 + DILM12, PKZM0 + DILM15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZM0 Accessory Wiring set

Catalog Number 283149

Model Code PKZM0-XDM12

EAN 4015082831493

Product Length/Depth 91 mm

Product Height 67 mm

Product Width 45 mm

Product Weight 0.058 kg

Certifications UL

UL File No.: E36332

CSA-C22.2 No. 14

CE

CSA

IEC/EN 60947-4-1

CSA Class No.: 3211-05

CSA File No.: 165628

UL 508

UL Category Control No.: NLRV

Catalog Notes Cannot be combined with NHI-E...PKZ0-PI. Ue ? 415 V

General information

Accessories Cable routing, main current wiring between PKZM0 and contactor with tool-less plug connection, mechanical connection element for PKZM0 and contactor included with supplied equipment.

Model Direct circuit

Product category Accessories

Product category Accessories

Type Wiring set

Climatic environmental conditions

Ambient operating temperature - min -25 °C

Ambient operating temperature - max 55 °C

Electrical rating

Rated operational current (Ie) 15 A

Rated operational voltage (Ue) - max 415 VAC

Design verification

Equipment heat dissipation, current-dependent P_{vid} 1.5 W

Heat dissipation capacity P_{diss} 0 W

Heat dissipation per pole, current-dependent P_{vid} 0.5 W

Rated operational current for specified heat dissipation (I_n) 15.5 A

Static heat dissipation, non-current-dependent P_{vs} 0 W

10.2.2 Corrosion resistance Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKZM0-XDM12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.