

**INDUSTRIAL COMPONENT DATA**

# PKZM0-XRM12 283185 Y7-283185 EATON ELECTRIC Kit, +component adapter, for reversing starter for DILM7-M12

Brand: EATON - MOELLER | Manufacturer Part Number: PKZM0-XRM12



|                 |                                      |
|-----------------|--------------------------------------|
| Manufacturer    | EATON - MOELLER                      |
| MPN / Reference | PKZM0-XRM12                          |
| Catalog number  | Y7-283185                            |
| Category        | Wiring set for power circuit breaker |
| Minimum order   | 1 Pcs                                |
| Document ID     | EO-0CA7620A88                        |
| Generated       | 2026-08-05                           |

## Product Overview

Kit, +component adapter, for reversing starter for DILM7-M12

PKZM0-XRM12

Eaton Moeller® series PKZM0 Wiring set, For reversing starters, DILM7-M12

Wiring set for reversing starter PKZM0 + DILM7-01. PKZM0 + DILM9-01, PKZM0 + DILM12-01

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | EATON - MOELLER > Circuit Breakers PKZ |
|--------------|----------------------------------------|

## Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZM0 Accessory Wiring set Catalog Number 283185 Model Code PKZM0-XRM12

EAN 4015082831851 Product Length/Depth 95 mm Product Height 67 mm Product Width 90 mm Product Weight 0.14 kg

Certifications CSA-C22.2 No. 14

IEC/EN 60947-4-1

CE

CSA Class No.: 3211-05

UL File No.: E36332

UL Category Control No.: NLRV

CSA

CSA File No.: 165628

UL

**UL 508 General**

Model Reversing switching Product category Accessories Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Electrical rating

Rated operational voltage (Ue) - max 415 VAC Design verification

Equipment heat dissipation, current-dependent P<sub>vid</sub> 1.5 W Heat dissipation capacity P<sub>diss</sub> 0 W Heat dissipation per pole, current-dependent P<sub>vid</sub> 0.5 W Rated operational current for specified heat dissipation (I<sub>n</sub>) 15.5 A Static heat dissipation, non-current-dependent P<sub>vs</sub> 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgea...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send EATON - MOELLER / PKZM0-XRM12 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.