

INDUSTRIAL COMPONENT DATA

KLV-F5UPP-HY24-4PR 302472 Y7-302472 EATON ELECTRIC

KLV-F5UPP-HY24-4PR

Brand: EATON - MOELLER | Manufacturer Part Number: KLV-F5UPP-HY24-4PR



Manufacturer	EATON - MOELLER
MPN / Reference	KLV-F5UPP-HY24-4PR
Catalog number	Y7-302472
Category	Accessories/spare parts for small distribution board
Minimum order	1 Pcs
Document ID	EO-632CD939F7
Generated	2026-08-06

Product Overview

KLV-F5UPP-HY24-4PR

Eaton xComfort KLV LV systems Final Distribution Boards. Flush-mounting expansion kit F, Hybrid 5-row, 24MU, form of delivery for projects

Form of delivery for projects: Flush mounting expansion kit for 5-row Hybrid KLV compact distribution boards, 24MU, flat door frame design, equipment supplied: device carrier, front cover, neutral and protective conductor terminals with KSK plug-in terminal technology, micro-perforated mounting plate, device holder, single socket, 3D adjustment element for mounting designed to adjust the mounting depth by up to 18 mm, cable retainer, installation instructions, label sheet.

Standards: Complete distribution board in accordance with IEC/EN 60670-24, IEC/EN 62208 and therefore approved for distribution boards as defined in IEC/EN 61439-3 . To obtain protection class II, all devices installed on the mounting plate must be of the fully insulated type.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Compact Distribution Boxes

Additional Product Information

General specifications

Product Name Eaton xComfort KLV project delivery form Catalog Number 302472 Model Code KLV-F5UPP-HY24-4PR
EAN 9010238161375 Product Length/Depth 65 mm Product Height 840 mm Product Width 360 mm Product Weight 5.57 kg
Compliances Conform

RoHS conform Certifications IEC/EN 62208, IEC/EN 60670-24 (PD) Product specifications

Special features IP30Protection Class IIPlastic housing Type Basic deviceInstallation distribution boardsKLV for projects

Accessory/spare part type Other
Accessory Fitted with: Imprintable sheet
Microperforated mounting plate
1x single-way socket outlet
Installation instructions
3D adjustment element for mounting
Neutral-/protective conductor terminal
Front cover
Cable retainer
Device holder
Device support rails
Door/Frame Frequency rating 50 Hz Used with Basic device
KLV for projects
Installation distribution boards Color White (RAL 9016)
White Degree of protection IP30
IK05 (impact resistance) Terminal type Plug-in terminals Ambient operating temperature details -5 °C - 40 °C Application
Indoor Cover/door color White Material Polystyren (plastic)
Sheet steel, powder-coated Number of rows 5 Installation type Flush mounting Mounting method Flush mounting Functions
Basic device
Additional equipment Number of module space units per row 12 Protection class II (totally insulated) Protective shrouding
material Plastic PE and N terminal number and cross section PE: 2 x (2.5 mm² - 25 mm²) + 14 x (0.5 mm² - 4 mm²)
N: 2 x (2.5 mm² - 25mm²) + 14...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / KLV-F5UPP-HY24-4PR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.