

INDUSTRIAL COMPONENT DATA

KLV-SF5HWP-HY24-4PR 302475 Y7-302475 EATON ELECTRIC KLV-SF5HWP-HY24-4PR

Brand: EATON - MOELLER | Manufacturer Part Number: KLV-SF5HWP-HY24-4PR



Manufacturer	EATON - MOELLER
MPN / Reference	KLV-SF5HWP-HY24-4PR
Catalog number	Y7-302475
Category	Accessories/spare parts for small distribution board
Minimum order	1 Pcs
Document ID	EO-D0CB211E3D
Generated	2026-08-06

Product Overview

KLV-SF5HWP-HY24-4PR

Eaton xComfort KLV LV systems Final Distribution Boards. Hollow-wall expansion kit Hybrid 5-row, 24MU, form of delivery for projects, super flat door

Form of delivery for projects: Hollow-wall mounting expansion kit for 5-row Hybrid KLV compact distribution boards, 24MU, super-flat door frame design, equipment supplied: device carrier, front cover, neutral and protective conductor terminals with KSK plug-in terminal technology, micro-perforated mounting plate, device holder, single socket, 3D adjustment element for mounting designed to adjust the mounting depth by up to 18 mm, cable retainer, installation instructions, label sheet .

Standards: Complete distribution board in accordance with IEC/EN 60670-24, IEC/EN 62208 and therefore approved for distribution boards as defined in IEC/EN 61439-3. To obtain protection class II, all devices installed on the mounting plate must be of the fully insulated type.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Compact Distribution Boxes

Additional Product Information

General specifications

Product Name Eaton xComfort KLV project delivery form Catalog Number 302475 Model Code KLV-SF5HWP-HY24-4PR
EAN 9010238161405 Product Length/Depth 65 mm Product Height 840 mm Product Width 360 mm Product Weight 5.57 kg
Compliances Conform

RoHS conform Certifications IEC/EN 62208, IEC/EN 60670-24 (PD) Product specifications

Special features IP30Protection Class IIPlastic housing Type Basic deviceInstallation distribution boardsKLV for projects

Accessory/spare part type Other
Accessory Fitted with: Microperforated mounting plate
Neutral-/protective conductor terminal
3D adjustment element for mounting
Front cover
Cable retainer
Installation instructions
Imprintable sheet
Device holder
1x single-way socket outlet
Door/Frame
Device support rails Frequency rating 50 Hz Used with Installation distribution boards
Basic device
KLV for projects Color White
White (RAL 9016) Degree of protection IK05 (impact resistance)
IP30 Terminal type Plug-in terminals Ambient operating temperature details -5 °C - 40 °C Application Indoor Cover/door color White Material Sheet steel, powder-coated
Polystyren (plastic) Number of rows 5 Installation type Hollow-wall mounting Mounting method Hollow wall Functions Basic device
Additional equipment Number of module space units per row 12 Protection class II (totally insulated) Protective shrouding material Plastic PE and N terminal number and cross section N: 2 x (2.5 mm² - 25mm²) + 14 x (0.5 mm² - 4 mm²)
PE: 2 x (2.5 mm² - 25 mm²)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / KLV-SF5HWP-HY24-4PR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.