

INDUSTRIAL COMPONENT DATA

KLV-SF5UPP-HY36-4PR 302478 Y7-302478 EATON ELECTRIC

KLV-SF5UPP-HY36-4PR

Brand: EATON - MOELLER | Manufacturer Part Number: KLV-SF5UPP-HY36-4PR



Manufacturer	EATON - MOELLER
MPN / Reference	KLV-SF5UPP-HY36-4PR
Catalog number	Y7-302478
Category	Accessories/spare parts for small distribution board
Minimum order	1 Pcs
Document ID	EO-FF9D64AA53
Generated	2026-08-06

Product Overview

KLV-SF5UPP-HY36-4PR

Eaton xComfort KLV LV systems Final Distribution Boards. Flush-mounting expansion kit S, Hybrid 5-row, 36MU, form of delivery for projects

Form of delivery for projects: Flush mounting expansion kit for 5-row Hybrid KLV compact distribution boards, 36MU, super-flat door frame design, equipment supplied: device carrier, front cover, neutral and protective conductor terminals with KSK plug-in terminal technology, micro-perforated mounting plate, device holder, single socket, 3D adjustment element for mounting designed to adjust the mounting depth by up to 18 mm, cable retainer, installation instructions, label sheet.

Standards: Complete distribution board in accordance with IEC/EN 60670-24, IEC/EN 62208 and therefore approved for distribution boards as defined in IEC/EN 61439-3 . To obtain protection class II, all devices installed on the mounting plate must be of the fully insulated type.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Compact Distribution Boxes
--------------	--

Additional Product Information

General specifications

Product Name Eaton xComfort KLV project delivery form Catalog Number 302478 Model Code KLV-SF5UPP-HY36-4PR
EAN 9010238161429 Product Length/Depth 65 mm Product Height 840 mm Product Width 360 mm Product Weight 5.63 kg
Compliances Conform

RoHS conform Certifications IEC/EN 62208, IEC/EN 60670-24 (PD) Delivery program

Type Basic deviceInstallation distribution boardsKLV for projects Accessory/spare part type Other

Accessory Application Indoor Color White
White (RAL 9016) Technical data - electrical
Frequency rating 50 Hz Technical data - mechanical
Mounting method Flush mounting Material Sheet steel, powder-coated
Polystyren (plastic) Number of module space units per row 12 Number of rows 5 Terminal type Plug-in terminals PE and N
terminal number and cross section N: 4 x (2.5 mm² - 25 mm²) + 28 x (0.5 mm² - 4 mm²)
PE: 4 x (2.5 mm² - 25 mm²) + 28 x (0.5 mm² - 4 mm²) Cover/door color White Installation type Flush mounting Protective
shrouding material Plastic Design verification as per IEC/EN 61439 - technical data
Ambient operating temperature details -5 °C - 40 °C Additional information
Fitted with: Imprintable sheet
3D adjustment element for mounting
Neutral-/protective conductor terminal
Device holder
Installation instructions
Cable retainer
Microperforated mounting plate
Device support rails
1x single-way socket outlet
Front cover
Door/Frame Functions Basic device
Additional equipment Protection class II (totally insulated) Special features IP30Protec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / KLV-SF5UPP-HY36-4PR with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.