

## INDUSTRIAL COMPONENT DATA

# M22-XAK12 121086 Y7-121086 EATON ELECTRIC Label, emergency stop, D 90mm, yellow, DE, EN, ES, PT

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XAK12



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | EATON - MOELLER                |
| MPN / Reference | M22-XAK12                      |
| Catalog number  | Y7-121086                      |
| Category        | Text plate for command devices |
| Minimum order   | 1 Pcs                          |
| Document ID     | EO-3F18477997                  |
| Generated       | 2026-08-06                     |

## Product Overview

Label, emergency stop, D=90mm, yellow, DE, EN, ES, PT

M22-XAK12

Eaton Moeller® series M22 Label, emergency stop, D=90mm, yellow, DE, EN, ES, PT

Emergency stop label, Product range: Accessories, RAL 1004, Connection to SmartWire-DT: no

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

## Additional Product Information

## General specifications

Product Name Eaton Moeller® series M22 Accessory Emergency-Stop label Catalog Number 121086 Model Code M22-XAK12 EAN 4015081189168 Product Length/Depth 90 mm Product Height 1 mm Product Width 90 mm Product Weight 0.008 kg Certifications UL/CSA certification not required

DNV

GL

## LR Features &amp; Functions

Color Yellow Inscription EMERGENCY STOP Language Several RAL-number 1004 Shape Round General Degree of protection IP66 Product Category Accessories Size 90 x 90 mm Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication Connection to SmartWire-DT No Design verification Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation capacity Pdis 0 W Heat dissipation per pole,

current-dependent P<sub>vid</sub> 0 W Rated operational current for specified heat dissipation (I<sub>n</sub>) 0 A Static heat dissipation, non-current-dependent P<sub>vs</sub> 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Please enquire 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XAK12 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.