

## INDUSTRIAL COMPONENT DATA

# M22-XZK-DK99 216478 Y7-216478 EATON ELECTRIC Label, emergency switching off, yellow, HxW 50x33mm, NODSTOP

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XZK-DK99



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | EATON - MOELLER                |
| MPN / Reference | M22-XZK-DK99                   |
| Catalog number  | Y7-216478                      |
| Category        | Text plate for command devices |
| Minimum order   | 1 Pcs                          |
| Document ID     | EO-39459E1F3C                  |
| Generated       | 2026-08-06                     |

## Product Overview

Label, emergency switching off, yellow, HxW=50x33mm, NODSTOP

M22-XZK-DK99

Emergency-Stop label, Product range: Accessories, yellow, Connection to SmartWire-DT: no

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog pathEATON - MOELLER &gt; Auxiliary Control and Signalling Elements

## Additional Product Information

Label, emergency switching off, yellow, HxW=50x33mm, NODSTOPEmergency-Stop label, Product range: Accessories, yellow, Connection to SmartWire-DT: no

General specificationsProduct nameEaton Moeller® series M22 Accessory Emergency-Stop labelPart

no.M22-XZK-DK99EAN4015082164782Product Length/Depth50 millimetreProduct height1 millimetreProduct width33

millimetreProduct weight0.002 kilogramCertificationsUL/CSA certification not required

DNV

LR

GLProduct TradenameM22Product TypeAccessoryProduct Sub TypeEmergency-Stop labelFeatures &amp;

FunctionsColorYellowInscriptionEMERGENCY STOPLanguageGermanRAL-number1004ShapeRectangularGeneral

informationDegree of protectionIP66Size33 x 50 mmClimatic environmental conditionsAmbient operating temperature -

min-25 °CAmbient operating temperature - max70 °CCommunicationConnection to SmartWire-DTNoDesign

verificationEquipment heat dissipation, current-dependent Pvid0 WHeat dissipation capacity Pdisso WHeat dissipation per

pole, current-dependent Pvid0 WRated operational current for specified heat dissipation (In)0 AStatic heat dissipation,

non-current-dependent Pvs0 W10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2.3.2 Verification of resistance of insulating materials to normal heatMeets the product standard's requirements.10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effectsMeets the product standard'...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XZK-DK99 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.