


INDUSTRIAL COMPONENT DATA

M22-XCK3 290260 Y7-290260 EATON ELECTRIC Label, for 2 position switch, blank

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XCK3



Manufacturer	EATON - MOELLER
MPN / Reference	M22-XCK3
Catalog number	Y7-290260
Category	Text plate for command devices
Minimum order	10 Pcs
Document ID	EO-C9ECEE61CE
Generated	2026-08-04

Product Overview

Label, for 2 position switch, blank

M22-XCK3

Eaton Moeller® series M22 Label, for 2 position switch, blank

Label, Product range: Accessories, Single unit, Name: 2 direction arrows, can be turned through 90°, For use with: Joystick 2 positions, Connection to SmartWire-DT: no, Standards: IEC/EN 60947, VDE 0660, Mounting position: As required

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Label for 4-position switch Catalog Number 290260 Model Code M22-XCK3 EAN 4015082902605 Product Length/Depth 50 mm Product Height 2 mm Product Width 50 mm Product Weight 0.004 kg Certifications UL/CSA certification not required

VDE 0660

IEC/EN 60947

DNV

GL

LR Features & Functions

Color Silver Inscription Other

2 direction arrows, can be turned through 90° Language Other RAL-number 1004 Shape Square General

Degree of protection IP66 Product Category Accessories Used with Two-position joystick

M22-D4...

M22-DI4...

M22-WJ...

M22-WRJ...

M22S-WJ...

M22S-WRJ... Ambient conditions, mechanical

Mounting position As required Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Communication

Connection to SmartWire-DT No Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard'...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XCK3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.