

INDUSTRIAL COMPONENT DATA

SL7-L120-B 171467 Y7-171467 EATON ELECTRIC LED continuously light , blue 120V

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-L120-B



Manufacturer	EATON - MOELLER
MPN / Reference	SL7-L120-B
Catalog number	Y7-171467
Category	Optical module for signal tower
Minimum order	1 Pcs
Document ID	EO-6F4A94B5E6
Generated	2026-08-04

Product Overview

LED continuously light , blue 120V

SL7-L120-B

Eaton Moeller® series SL7 Continuous light module; blue; LED;120 V

Continuous light module, Color Blue, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: Ue= 110/120 V AC, Type of light: Continuous light, Light elements: LED, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL7 Continuous light module Catalog Number 171467 Model Code SL7-L120-B EAN 4015081677948 Product Length/Depth 73 mm Product Height 73 mm Product Width 73 mm Product Weight 0.082 kg

Compliances CE Marked Certifications CSA Certified

UL Listed

UL 508

cULus Listed

CSA Std. C22.2 No. 14-10

UL Listed file E29184

CSA Class No. NKCR7

CSA Std. C22.2 No. 94-91

IEC Rated

UL

UL File No.: E29184

CSA Class No.: NKCR7

CSA-C22.2 No. 14-10

Certified by UL for use in Canada

IEC/EN 60529

CSA-C22.2 No. 94-91

CE

UL report applies to both US and Canada

IEC/EN 60947-5-1

UL Category Control No.: NKCR Catalog Notes 0 Features & Functions

Color Blue Enclosure color Black Functions Continuous light Light modules LED Number of modules Max. 5 (with standard base)

Max. 10 (with base for mounting on both sides) General

Connection to SmartWire-DT No Current consumption 0.028 - 0.031 A, at 110/120 V AC Degree of protection NEMA 4X

IP66 Lifespan, electrical 100,000 h Light type Continuous light Material Cap: Polycarbonate (PC)

Enclosure: Polycarbonate (PC) Mounting position As required Overvoltage category III Pollution degree 3 Product Category

SL signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance Mechanical,

According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Type Continuous light module Voltage type AC

Climatic environmental conditions

Ambient o...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-L120-B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.