

INDUSTRIAL COMPONENT DATA

SL7-L230-G 171474 Y7-171474 EATON ELECTRIC LED continuously light , green 230V

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-L230-G



Manufacturer	EATON - MOELLER
MPN / Reference	SL7-L230-G
Catalog number	Y7-171474
Category	Optical module for signal tower
Minimum order	1 Pcs
Document ID	EO-751FABFE50
Generated	2026-08-05

Product Overview

LED continuously light , green 230V

SL7-L230-G

Continuous light module; green; LED;230 V

Continuous light module, Color green, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: Ue= 230/240 V AC, Type of light: Continuous light, Light elements: LED, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Continuous light module; green; LED;230 VContinuous light module, Color green, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: Ue= 230/240 V AC, Type of light: Continuous light, Light elements: LED, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

General specificationsProduct nameEaton Moeller® series SL7 Continuous light modulePart

no.SL7-L230-GEAN4015081678006Product Length/Depth73 millimetreProduct height73 millimetreProduct width73 millimetreProduct weight0.082 kilogramCertificationsCSA-C22.2 No. 94-91

UL Category Control No.: NKCR

UL report applies to both US and Canada

IEC/EN 60947-5-1

CSA Class No.: NKCR7

CE

UL 508

UL

CSA-C22.2 No. 14-10

Certified by UL for use in Canada

UL File No.: E29184

IEC/EN 60529Product TradenameSL7Product TypeContinuous light moduleProduct Sub TypeNoneFeatures & FunctionsColorGreenEnclosure colorBlackFunctionsContinuous lightLight modulesLEDNumber of modulesMax. 10 (with base for mounting on both sides)

Max. 5 (with standard base)General informationConnection to SmartWire-DTNoCurrent consumption0.027 - 0.028 A, at 230/240 V ACDegree of protectionNEMA 13

IP66Lifespan, electrical100,000 hLight typeContinuous lightMaterialEnclosure: Polycarbonate (PC)

Cap: Polycarbonate (PC)Mounting positionAs requiredOvervoltage categoryIIIPollution degree3Product CategorySL signal towersRadiation angle360 °Rated impulse withstand voltage (Uimp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-L230-G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.