

INDUSTRIAL COMPONENT DATA

SL4-L24-A 171318 Y7-171318 EATON ELECTRIC LED continuously light , orange 24V

Brand: EATON - MOELLER | Manufacturer Part Number: SL4-L24-A



Manufacturer	EATON - MOELLER
MPN / Reference	SL4-L24-A
Catalog number	Y7-171318
Category	Optical module for signal tower
Minimum order	1 Pcs
Document ID	EO-3B73C05D11
Generated	2026-08-05

Product Overview

LED continuously light , orange 24V

SL4-L24-A

Eaton Moeller® series SL4 Continuous light module; orange; LED;24 V

Continuous light module, Color Orange, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: $U_e = 24$ V AC/DC, Type of light: Continuous light, Light elements: LED, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL4 Continuous light module Catalog Number 171318 Model Code SL4-L24-A EAN 4015081678570 Product Length/Depth 43 mm Product Height 75 mm Product Width 43 mm Product Weight 0.042 kg

Compliances CE Marked Certifications UL 508

UL Listed

CSA Certified

cULus Listed

UL Listed file E29184

CSA Std. C22.2 No. 94-91

CSA Class No. NKCR7

CSA Std. C22.2 No. 14-10

IEC Rated

IEC/EN 60529

CSA-C22.2 No. 14-10

CE

UL report applies to both US and Canada

CSA-C22.2 No. 94-91

Certified by UL for use in Canada

UL File No.: E29184

UL Category Control No.: NKCR

CSA Class No.: NKCR7

IEC/EN 60947-5-1

UL Catalog Notes 0 Features & Functions

Color Orange Enclosure color Black Functions Continuous light Light modules LED Number of modules Max. 10 (with base for mounting on both sides)

Max. 5 (with standard base) General

Connection to SmartWire-DT No Current consumption 0.022 - 0.033 A, at 24 V AC/DC Degree of protection IP66

NEMA 13 Lifespan, electrical 100,000 h Light type Continuous light Material Enclosure: Polycarbonate (PC)

Cap: Polycarbonate (PC) Mounting position As required Overvoltage category III Pollution degree 3 Product Category SL

signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Type Continuous light module Voltage type AC/DC Climatic environmental conditions

Ambient...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL4-L24-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.