

INDUSTRIAL COMPONENT DATA

SL4-L120-R 171321 Y7-171321 EATON ELECTRIC LED continuously light , red 120V

Brand: EATON - MOELLER | Manufacturer Part Number: SL4-L120-R



Manufacturer	EATON - MOELLER
MPN / Reference	SL4-L120-R
Catalog number	Y7-171321
Category	Optical module for signal tower
Minimum order	1 Pcs
Document ID	EO-0A0097C756
Generated	2026-08-05

Product Overview

LED continuously light , red 120V

SL4-L120-R

Eaton Moeller® series SL4 Continuous light module; red; LED;120 V

Continuous light module, Color Red, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: Ue= 110/120 V AC, Type of light: Continuous light, Light elements: LED, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL4 Continuous light module Catalog Number 171321 Model Code SL4-L120-R EAN 4015081678600 Product Length/Depth 43 mm Product Height 75 mm Product Width 43 mm Product Weight 0.043 kg

Certifications UL report applies to both US and Canada

IEC/EN 60529

UL Category Control No.: NKCR

IEC/EN 60947-5-1

Certified by UL for use in Canada

CSA-C22.2 No. 14-10

CE

UL
CSA Class No.: NKCR7
CSA-C22.2 No. 94-91
UL 508
UL File No.: E29184 Features & Functions
Color Red Enclosure color Black Functions Continuous light Light modules LED Number of modules Max. 5 (with standard base)
Max. 10 (with base for mounting on both sides) General
Connection to SmartWire-DT No Current consumption 45 mA at 110/120 V AC Degree of protection NEMA 4
IP66 Lifespan, electrical 100,000 h Light type Continuous light Material Enclosure: Polycarbonate (PC)
Cap: Polycarbonate (PC) Mounting position As required Overvoltage category III Pollution degree 3 Product Category SL
signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance 15 g, Mechanical,
According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Mechanical, According to IEC/EN 60068-2-27 Type Continuous light module Voltage type AC Climatic environmental
conditions
Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat,
constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30 Electrical rating
Le...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL4-L120-R with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.