INDUSTRIAL COMPONENT DATA

SL7-L24-W 171464 Y7-171464 EATON ELECTRIC LED continuously light , white 24V

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-L24-W

Manufacturer	EATON - MOELLER
MPN / Reference	SL7-L24-W
Catalog number	Y7-171464
Category	Optical module for signal tower
Minimum order	1 Pcs
Document ID	EO-B8AC187A1B
Generated	2026-08-04

Product Overview

LED continuously light , white 24V
SL7-L24-W
Eaton Moeller® series SL7 Continuous light module;white; LED;24 V
Continuous light module, Color Clear, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: Ue= 24 V AC/DC, Type of light: Continuous light, Light elements: LED, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications
Product Name Eaton Moeller® series SL7 Continuous light module Catalog Number 171464 Model Code SL7-L24-W EAN 4015081677917 Product Length/Depth 73 mm Product Height 73 mm Product Width 73 mm Product Weight 0.08 kg
Certifications CE
UL 508
Certified by UL for use in Canada
UL File No.: E29184
UL report applies to both US and Canada
UL Category Control No.: NKCR
IEC/EN 60529

IEC/EN 60947-5-1
CSA-C22.2 No. 14-10
CSA-C22.2 No. 94-91
UL
CSA Class No.: NKCR7 Features & Functions
Color Other Enclosure color Black Functions Continuous light Light modules LED Number of modules Max. 10 (with base for mounting on both sides)
Max. 5 (with standard base) General
Connection to SmartWire-DT No Current consumption 50 mA at 24 V AC/DC Degree of protection IP66
NEMA 4 Lifespan, electrical 100,000 h Light type Continuous light Material Cap: Polycarbonate (PC)
Enclosure: Polycarbonate (PC) Mounting position As required Overvoltage category III Pollution degree 3 Product Category SL signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Mechanical, According to IEC/EN 60068-2-27 Type Continuous light module Voltage type AC/DC Climatic environmental conditions
Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Electrical rating
L...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-L24-W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.