

INDUSTRIAL COMPONENT DATA

M22-CLEDC230-R 216579 Y7-216579 EATON ELECTRIC LED element, red, base fixing, cage clamp

Brand: EATON - MOELLER | Manufacturer Part Number: M22-CLEDC230-R



Manufacturer	EATON - MOELLER
MPN / Reference	M22-CLEDC230-R
Catalog number	Y7-216579
Category	Lamp holder block for control circuit devices
Minimum order	20 Pcs
Document ID	EO-97F8BDD281
Generated	2026-08-02

Product Overview

LED element, red, base fixing, cage clamp

M22-CLEDC230-R

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

LED element, red, base fixing, cage clampLED element, Fixing: Base fixing, Connection technique: Cage Clamp, Description: Cage Clamp is a registered trademark of Wago Kontakttechnik GmbH/Minden, Germany, Rated operational voltage: $U_e = 85 - 264 \text{ V AC}$, 50/60 Hz V, Rated operational current: $I_e = 5 - 15 \text{ mA}$, Power consumption: $P_{max} = 0.33 \text{ W}$, At 230 V, Degree of Protection: IP20, Connection to SmartWire-DT: no, Standards: IEC 60947-5-1

General specificationsProduct nameEaton Moeller® series M22 Accessory LEDPart no.M22-CLEDC230-REAN4015082165796Product Length/Depth39 millimetreProduct height39 millimetreProduct width10 millimetreProduct weight0.01 kilogramCompliancesCE MarkedCertificationsCSA Std. C22.2 No. 94-91 CSA Std. C22.2 No. 14-05 EN 60947-5 UL 508 IEC 60947-5 VDE UL Category Control No.: NKCR IEC 60947-5-1

IEC/EN 60947-5

CE

CSA File No.: 012528

UL

CSA-C22.2 No. 94-91

CSA Class No.: 3211-03

CSA-C22.2 No. 14-05

UL File No.: E29184

CSAProduct TradenameM22Product TypeAccessoryProduct Sub TypeLEDCatalog NotesCage Clamp is a registered trademark of Wago Kontakttechnik GmbH/Minden, GermanyFeatures & FunctionsFitted with:Diode

Light sourceLight colorRedGeneral informationDegree of protectionIP20Lifespan, electrical100,000 h (at 25°C, according to EN60064)Operating torque0.8 N·mOvervoltage categoryIIIPollution degree3Rated impulse withstand voltage (Uimp)6000 V ACVoltage typeACAmbient conditions, mechanicalMounting positionAs requiredShock resistanceMechanical, According to IEC/EN 6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-CLEDC230-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.