INDUSTRIAL COMPONENT DATA

SL7-BL120-W 171393 Y7-171393 EATON ELECTRIC LED flashing light, white 120V

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-BL120-W

Manufacturer	EATON - MOELLER
MPN / Reference	SL7-BL120-W
Catalog number	Y7-171393
Category	Optical module for signal tower
Minimum order	1 Pcs
Document ID	EO-43763D8647
Generated	2026-08-03

Product Overview

LED flashing light, white 120V
SL7-BL120-W
Eaton Moeller® series SL7 Flashing light module, white, LED, 120 V
Flashing light module, Color Clear, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: Ue= 110/120 V AC, Type of light: Flashing light, Light elements: LED, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications
Product Name Eaton Moeller® series SL7 Flashing light module Catalog Number 171393 Model Code SL7-BL120-W EAN 4015081679270 Product Length/Depth 73 mm Product Height 73 mm Product Width 73 mm Product Weight 0.082 kg
Certifications CE
UL report applies to both US and Canada
UL
CSA Class No.: NKCR7
CSA-C22.2 No. 94-91
UL 508
UL File No.: E29184

IEC/EN 60947-5-1
CSA-C22.2 No. 14-10
Certified by UL for use in Canada
UL Category Control No.: NKCR
IEC/EN 60529 Features & Functions
Color Other Enclosure color Black Functions Blinker light Light modules LED Number of modules Max. 10 (with base for mounting on both sides)
Max. 5 (with standard base) General
Connection to SmartWire-DT No Current consumption 45 mA at 110/120 V AC Degree of protection NEMA 4X
IP66 Flashing frequency 2 Hz Lifespan, electrical 100,000 h Light type Flashing light Material Cap: Polycarbonate (PC)
Enclosure: Polycarbonate (PC) Mounting position As required Overvoltage category III Pollution degree 3 Product Category
SL signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance 15 g,
Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Mechanical, According to IEC/EN 60068-2-27 Type Flashing light module Voltage type AC Climatic environmental conditions
Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30 E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-BL120-W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.