

INDUSTRIAL COMPONENT DATA

SL4-BL24-W 171340 Y7-171340 EATON ELECTRIC LED flashing light, white 24V

Brand: EATON - MOELLER | Manufacturer Part Number: SL4-BL24-W



Manufacturer	EATON - MOELLER
MPN / Reference	SL4-BL24-W
Catalog number	Y7-171340
Category	Optical module for signal tower
Minimum order	1 Pcs
Document ID	EO-5BB99F89FB
Generated	2026-08-03

Product Overview

LED flashing light, white 24V

SL4-BL24-W

Eaton Moeller® series SL4 Flashing light module, white, LED, 24 V

Flashing light module, Color Clear, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: $U_e = 24$ V AC/DC, Type of light: Flashing light, Light elements: LED, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL4 Flashing light module Catalog Number 171340 Model Code SL4-BL24-W EAN 4015081678761 Product Length/Depth 43 mm Product Height 75 mm Product Width 43 mm Product Weight 0.042 kg

Certifications UL 508

UL report applies to both US and Canada

UL

UL Category Control No.: NKCR

UL File No.: E29184

Certified by UL for use in Canada

IEC/EN 60947-5-1

CSA-C22.2 No. 94-91

CSA Class No.: NKCR7

IEC/EN 60529

CE

CSA-C22.2 No. 14-10 Features & Functions

Color Other Enclosure color Black Functions Blinker light Light modules LED Number of modules Max. 10 (with base for mounting on both sides)

Max. 5 (with standard base) General

Connection to SmartWire-DT No Current consumption 0.028 - 0.036 A, at 24 V AC/DC Degree of protection IP66

NEMA 4X Flashing frequency 2 Hz Lifespan, electrical 100,000 h Light type Flashing light Material Cap: Polycarbonate (PC)

Enclosure: Polycarbonate (PC) Mounting position As required Overvoltage category III Pollution degree 3 Product Category

SL signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance 15 g,

Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Type Flashing light module Voltage type AC/DC Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL4-BL24-W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.