

INDUSTRIAL COMPONENT DATA

SL4-FL24-G-M 171374 Y7-171374 EATON ELECTRIC LED multistrobe light, green 24V

Brand: EATON - MOELLER | Manufacturer Part Number: SL4-FL24-G-M



Manufacturer	EATON - MOELLER
MPN / Reference	SL4-FL24-G-M
Catalog number	Y7-171374
Category	Optical module for signal tower
Minimum order	1 Pcs
Document ID	EO-5D6D09887F
Generated	2026-08-03

Product Overview

LED multistrobe light, green 24V

SL4-FL24-G-M

Eaton Moeller® series SL4 LED multistrobe light, green 24V

Multi-strobe light module, Color green, LED for effective signaling effect, With various strobe sequences, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: Ue= 24 V AC/DC, Type of light: Multistrobe light, Light elements: LED, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL4 Multi-strobe light module Catalog Number 171374 Model Code SL4-FL24-G-M
EAN 4015081679041 Product Length/Depth 43 mm Product Height 75 mm Product Width 43 mm Product Weight 0.042 kg
Certifications UL Category Control No.: NKCR

IEC/EN 60947-5-1

UL 508

CE

Certified by UL for use in Canada

UL File No.: E29184

CSA-C22.2 No. 94-91

IEC/EN 60529

UL

UL report applies to both US and Canada

CSA Class No.: NKCR7

CSA-C22.2 No. 14-10 Features & Functions

Color Green Enclosure color Black Features Various strobe sequences Functions Flash light Light modules LED Number of modules Max. 5 (with standard base)

Max. 10 (with base for mounting on both sides) General

Connection to SmartWire-DT No Current consumption max. 165 mA at 24 V AC/DC Degree of protection NEMA 13

IP66 Flashing frequency 1 - 2.6 Hz Lifespan, electrical 100,000 h Light type Multistrobe light Material Enclosure:

Polycarbonate (PC)

Cap: Polycarbonate (PC) Mounting position As required Overvoltage category III Pollution degree 3 Product Category SL signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Type Voltage type AC/DC Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp he...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL4-FL24-G-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.