

INDUSTRIAL COMPONENT DATA

SL4-FL230-B 171367 Y7-171367 EATON ELECTRIC Strobe light module blue LED 230 V

Brand: EATON - MOELLER | Manufacturer Part Number: SL4-FL230-B



Manufacturer	EATON - MOELLER
MPN / Reference	SL4-FL230-B
Catalog number	Y7-171367
Category	Optical module for signal tower
Minimum order	1 Pcs
Document ID	EO-F309156453
Generated	2026-08-02

Product Overview

Strobe light module; blue; LED;230 V

SL4-FL230-B

Strobe light module, Color Blue, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: Ue= 230/240 V AC, Type of light: Strobe light, Light elements: LED, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Strobe light module; blue; LED;230 VStrobe light module, Color Blue, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: Ue= 230/240 V AC, Type of light: Strobe light, Light elements: LED, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

General specificationsProduct nameEaton Moeller® series SL4 Strobe light modulePart

no.SL4-FL230-BEAN4015081678983Product Length/Depth43 millimetreProduct height75 millimetreProduct width43 millimetreProduct weight0.044 kilogramCertificationsCE

IEC/EN 60529

UL report applies to both US and Canada

IEC/EN 60947-5-1

UL

CSA Class No.: NKCR7

UL 508

CSA-C22.2 No. 14-10

UL File No.: E29184

UL Category Control No.: NKCR

Certified by UL for use in Canada

CSA-C22.2 No. 94-91Product TradenameSL4Product TypeStrobe light moduleProduct Sub TypeNoneFeatures & FunctionsColorBlueEnclosure colorBlackFunctionsFlash lightLight modulesLEDNumber of modulesMax. 10 (with base for mounting on both sides)

Max. 5 (with standard base)General informationConnection to SmartWire-DTNoCurrent consumption0.1 A, at 230/240 V ACDegree of protectionNEMA 13

IP66Flashing frequency1.4 HzLifespan, electrical100,000 hLight typeStrobe lightMaterialCap: Polycarbonate (PC)

Enclosure: Polycarbonate (PC)Mounting positionAs requiredOvervoltage categoryIIIPollution degree3Product CategorySL signal towersRadiation angle360 °Rated impulse withstand voltage (Uimp)4000 V ACShock r...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL4-FL230-B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.