

INDUSTRIAL COMPONENT DATA

SL7-FL230-G 171415 Y7-171415 EATON ELECTRIC Strobe light module green LED 230 V

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-FL230-G



Manufacturer	EATON - MOELLER
MPN / Reference	SL7-FL230-G
Catalog number	Y7-171415
Category	Optical module for signal tower
Minimum order	1 Pcs
Document ID	EO-E5091FC7B3
Generated	2026-08-03

Product Overview

Strobe light module; green; LED;230 V

SL7-FL230-G

Eaton Moeller® series SL7 Strobe light module; green; LED;230 V

Strobe light module, Color green, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: Ue= 230/240 V AC, Type of light: Strobe light, Light elements: LED, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL7 Strobe light module Catalog Number 171415 Model Code SL7-FL230-G EAN 4015081679461 Product Length/Depth 73 mm Product Height 73 mm Product Width 73 mm Product Weight 0.083 kg

Compliances CE Marked Certifications UL 508

CSA Certified

UL Listed

cULus Listed

UL Listed file E29184

CSA Std. C22.2 No. 94-91

CSA Std. C22.2 No. 14-10

CSA Class No. NKCR7

IEC Rated

UL Category Control No.: NKCR

IEC/EN 60947-5-1

CSA-C22.2 No. 14-10

UL report applies to both US and Canada

CE

Certified by UL for use in Canada

CSA Class No.: NKCR7

UL

UL File No.: E29184

CSA-C22.2 No. 94-91

IEC/EN 60529 Catalog Notes 0 Features & Functions

Color Green Enclosure color Black Functions Flash light Light modules LED Number of modules Max. 5 (with standard base)

Max. 10 (with base for mounting on both sides) General

Connection to SmartWire-DT No Current consumption 0.01 A, at 230/240 V AC Degree of protection NEMA 4

IP66 Flashing frequency 1.4 Hz Frequency rating 1.4 Hz Lifespan, electrical 100,000 h Light type Strobe light Material Cap: Polycarbonate (PC)

Enclosure: Polycarbonate (PC) Mounting position As required Overvoltage category III Pollution degree 3 Product Category SL signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Type Strobe light module Voltage type AC Climatic environme...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-FL230-G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.