

INDUSTRIAL COMPONENT DATA

SL7-FL24-G-HP 171421 Y7-171421 EATON ELECTRIC Strobe light module green high power LED 24 V

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-FL24-G-HP



Manufacturer	EATON - MOELLER
MPN / Reference	SL7-FL24-G-HP
Catalog number	Y7-171421
Category	Optical module for signal tower
Minimum order	1 Pcs
Document ID	EO-D1A0B36DAB
Generated	2026-08-05

Product Overview

Strobe light module; green;high power LED;24 V

SL7-FL24-G-HP

Eaton Moeller® series SL7 Strobe light module; green;high power LED;24 V

Strobe light module, Color green, High-performance LED for maximum signaling effect, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: Ue= 24 V AC/DC, Type of light: Strobe light, Light elements: High Performance LED, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL7 Strobe light module Catalog Number 171421 Model Code SL7-FL24-G-HP EAN 4015081679508 Product Length/Depth 73 mm Product Height 73 mm Product Width 73 mm Product Weight 0.09 kg

Certifications UL report applies to both US and Canada

Certified by UL for use in Canada

CSA-C22.2 No. 14-10

UL Category Control No.: NKCR

UL File No.: E29184

CE

UL 508

CSA-C22.2 No. 94-91

IEC/EN 60529

UL

CSA Class No.: NKCR7

IEC/EN 60947-5-1 Features & Functions

Color Green Enclosure color Black Functions Flash light Light modules High Performance LED Number of modules Max. 10
(with base for mounting on both sides)

Max. 5 (with standard base) General

Connection to SmartWire-DT No Current consumption max. 130 mA at 24 V AC/DC Degree of protection IP66

NEMA 13 Flashing frequency 1.4 Hz Lifespan, electrical 50,000 h Light type Strobe light Material Cap: Polycarbonate (PC)

Enclosure: Polycarbonate (PC) Mounting position As required Overvoltage category III Pollution degree 3 Product Category

SL signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance 15 g,

Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Type Voltage type AC/DC Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat,
cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Ele...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-FL24-G-HP with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.