

## INDUSTRIAL COMPONENT DATA

# SL7-FL230-R 171416 Y7-171416 EATON ELECTRIC Strobe light module red LED 230 V

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-FL230-R



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | EATON - MOELLER                 |
| MPN / Reference | SL7-FL230-R                     |
| Catalog number  | Y7-171416                       |
| Category        | Optical module for signal tower |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-6511D41659                   |
| Generated       | 2026-08-05                      |

## Product Overview

Strobe light module; red; LED;230 V

SL7-FL230-R

Eaton Moeller® series SL7 Strobe light module; red; LED;230 V

Strobe light module, Color Red, Product range: SL signal towers, Degree of Protection: IP66, Protection type UL: Type 4, 4X, 13, Rated operational voltage: Ue= 230/240 V AC, Type of light: Strobe light, Light elements: LED, Mounting position: As required, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

## Additional Product Information

General specifications

Product Name Eaton Moeller® series SL7 Strobe light module Catalog Number 171416 Model Code SL7-FL230-R EAN 4015081678266 Product Length/Depth 73 mm Product Height 73 mm Product Width 73 mm Product Weight 0.083 kg

Compliances CE Marked Certifications UL Listed

CSA Certified

cULus Listed

UL 508

UL Listed file E29184

CSA Std. C22.2 No. 94-91

CSA Std. C22.2 No. 14-10

CSA Class No. NKCR7

IEC Rated

UL report applies to both US and Canada

UL Category Control No.: NKCR

UL

CE

IEC/EN 60529

IEC/EN 60947-5-1

CSA Class No.: NKCR7

CSA-C22.2 No. 94-91

Certified by UL for use in Canada

CSA-C22.2 No. 14-10

UL File No.: E29184 Catalog Notes 0 Features & Functions

Color Red Enclosure color Black Functions Flash light Light modules LED Number of modules Max. 10 (with base for mounting on both sides)

Max. 5 (with standard base) General

Connection to SmartWire-DT No Current consumption 0.01 A, at 230/240 V AC Degree of protection NEMA 4

IP66 Flashing frequency 1.4 Hz Frequency rating 1.4 Hz Lifespan, electrical 100,000 h Light type Strobe light Material

Enclosure: Polycarbonate (PC)

Cap: Polycarbonate (PC) Mounting position As required Overvoltage category III Pollution degree 3 Product Category SL

signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance Mechanical,

According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Type Strobe light module Voltage type AC

Climatic environment...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-FL230-R with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.