

INDUSTRIAL COMPONENT DATA

SL7-FL24-R-HP 171422 Y7-171422 EATON ELECTRIC Strobe light module red high power LED 24 V

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-FL24-R-HP



Manufacturer	EATON - MOELLER
MPN / Reference	SL7-FL24-R-HP
Catalog number	Y7-171422
Category	Optical module for signal tower
Minimum order	1 Pcs
Document ID	EO-FF2FF6E216
Generated	2026-08-05

Product Overview

Strobe light module; red;high power LED;24 V

SL7-FL24-R-HP

Eaton Moeller® series SL7 Strobe light module; red;high power LED;24 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL7 Strobe light module Catalog Number 171422 Model Code SL7-FL24-R-HP EAN 4015081679515 Product Length/Depth 73 mm Product Height 73 mm Product Width 73 mm Product Weight 0.09 kg

Certifications CE

CSA Class No.: NKCR7

IEC/EN 60529

UL 508

CSA-C22.2 No. 94-91

IEC/EN 60947-5-1

UL report applies to both US and Canada

UL Category Control No.: NKCR

UL File No.: E29184

Certified by UL for use in Canada

CSA-C22.2 No. 14-10

UL Features & Functions

Color Red Enclosure color Black Functions Flash light Light modules High Performance LED Number of modules Max. 5 (with standard base)

Max. 10 (with base for mounting on both sides) General

Connection to SmartWire-DT No Current consumption 0.26 - 0.265 A, at 24 V AC/DC Degree of protection NEMA 4

IP66 Flashing frequency 1.4 Hz Lifespan, electrical 50,000 h Light type Strobe light Material Enclosure: Polycarbonate (PC)

Cap: Polycarbonate (PC) Mounting position As required Overvoltage category III Pollution degree 3 Product Category SL signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Type Voltage type AC/DC Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 El...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-FL24-R-HP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.