

INDUSTRIAL COMPONENT DATA

M22-XL-Y 216456 Y7-216456 EATON ELECTRIC Lens, indicator light, yellow, flush

Brand: EATON - MOELLER | Manufacturer Part Number: M22-XL-Y



Manufacturer	EATON - MOELLER
MPN / Reference	M22-XL-Y
Catalog number	Y7-216456
Category	Hood/lens for circuit control devices
Minimum order	10 Pcs
Document ID	EO-0CA8E6A0DA
Generated	2026-08-05

Product Overview

Lens, indicator light, yellow, flush

M22-XL-Y

Eaton Moeller® series M22 Lens, indicator light, yellow, flush

Single-color surface RMQ-Titan indicator light color lens. Fits on the front element of the indicator light. Can, e.g., be used as a replacement as well as for changing the color of an indicator light. Is approved for use world wide. inscribed button strip of the RMQ-Titan 22 mm program for use with illuminated pushbutton actuators with LED elements switched behind them.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Lens Catalog Number 216456 Model Code M22-XL-Y EAN 4015082164560 Product Length/Depth 29 mm Product Height 9 mm Product Width 29 mm Product Weight 0.002 kg

Certifications UL/CSA certification not required Features & Functions

Color Yellow Design Flat

Flush Inscription Individual inscription possible: <= 5 characters: letter height 5 mm

Individual inscription possible: > 5 characters: letter height 3 mm Inscription type Blank Lens color Yellow General

Product category Accessories Type Lenses for indicator lights Used with M22-L-X

M22-LC-X Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Communication

Connection to SmartWire-DT No Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to u...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-XL-Y with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.