

INDUSTRIAL COMPONENT DATA

EMR4-N500-2-B 221790 EATON ELECTRIC Liquid level monitoring relay, 2W, 220-240V50/60Hz, 250-500Ohm

Brand: EATON - MOELLER | Manufacturer Part Number: EMR4-N500-2-B



Manufacturer	EATON - MOELLER
MPN / Reference	EMR4-N500-2-B
Catalog number	221790
Category	(Fill) level monitoring relay
Minimum order	1 Pcs
Document ID	EO-1963756A79
Generated	2026-08-06

Product Overview

Liquid level monitoring relay, 2W, 220-240V50/60Hz, 250-500Ohm

Fluid level monitoring relay; 2 W; 220-240 V 50/60 Hz; 250-500 Ohm

Liquid level monitoring relay for monitoring the fill level or ratio of mixtures of conductive liquids convertible dry-running protection, protection against overflow 250kOhm-500kOhm selectable operating and release delay 0.5-10s, supply voltage 24-240 V AC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Relay timers (KETR, KEMR, KESR)

Additional Product Information

Liquid level monitoring relay, 2W, 220-240V50/60Hz, 250-500Ohm Alternate Catalog No. EMR4-N500-2-B EL-Nummer (Norway) 4110398 Liquid level monitoring relay for monitoring the fill level or ratio of mixtures of conductive liquids convertible dry-running protection, protection against overflow 250kOhm-500kOhm selectable operating and release delay 0.5-10s, supply voltage 24-240 V AC/DC [Delivery program

This item will continue to be available for a limited time only and is being replaced by the following item: 184757,

EMR6-N1000-A-1 Product range EMR Measuring and monitoring relays Basic function Level monitoring relays

On-delay/off-delay: adjustable between 0.1 - 10 s Monitoring of Fill level of conductive liquids

Mixture ratio of conductive liquids adjustable sensitivity range 250 ? - 500 k? Contact sequence Supply voltage 220 - 240 V AC, 50/60 Hz Width 45 mm , Technical data

Technical data in sheet catalogue Other technical data (sheet catalogue) Level monitoring relays , Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 5 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -25 °C Operating ambient temperature max. +60 °C IEC/EN 61439 design verification 10.2 Strength of materials and parts 10.2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMR4-N500-2-B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.