

INDUSTRIAL COMPONENT DATA

BXS35 EATON ELECTRIC Fuse-link, low voltage, 35 A, AC 440 V, 26 x 100 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: BXS35



Manufacturer	EATON - MOELLER
MPN / Reference	BXS35
Catalog number	10000
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-33E9C6B65C
Generated	2026-08-06

Product Overview

Fuse-link, low voltage, 35 A, AC 440 V, 26 x 100 mm, gL/gG, BS

35AMP BXS FUSELINK FOR SASIL FUSE SWITCH

Fuse, Fuse-link, low voltage, 35 A, AC 440 V, 26 x 100 mm, gL/gG, BS, cylindrical, offset-bolted tags, for SASIL fuse switch, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories
--------------	---

Additional Product Information

Fuse-link, low voltage, 35 A, AC 440 V, 26 x 100 mm, gL/gG, BS
Fuse-link, low voltage, 35 A, AC 440 V, 26 x 100 mm, gL/gG, BS, cylindrical, offset-bolted tags, for SASIL fuse switch, Breaking Capacity 80 kA

General specifications
Product name Eaton Bussmann series low voltage British standard fuse
Part no. BXS35EAN5027590493147

Product Length/Depth 27 millimetre
Product height 27 millimetre
Product width 78.5 millimetre

Product weight 64.6 gram
Compliance CE
Product Tradename None
Product Type Low voltage British standard fuse

Product Sub Type None
Electrical data
Amperage Rating 35 A
Voltage rating 440 V
Voltage type AC
Breaking capacity 80 kA
Class Class gG/gL
Product specifications
Application for SASIL fuse switch
Fuse type BXS
Connection Bolt-on
Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)
Electric engineering, automation, process control

engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) ()

[BAB264011])
Fuse construction type according to IEC 60269
Other Type of current AC
Rated voltage AC 440 V
Rated voltage DC

Rated current 35 A
Utilization category gL/gG (cable protection/equipment protection)
Breaking capacity 80 kA
Colour

codeNoneType of fuse status indicatorNonePower loss at rated currentWMounting holesCentre-to-centre distance of connectionsmm

ETIM for BXS35 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type accord...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BXS35 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.